



**DECLARATION OF PERFORMANCE**  
**In accordance with annex III of Regulation (EU) 305/2011**

**No. 000070**

1. Unique identification code of the product-type:

**ARDEX ST**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**See batch number and date of manufacture on packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Sealant for joints for facades, sanitary areas and pedestrian walkways.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**ARDEX UK Ltd,  
Homefield Road,  
Haverhill,  
Suffolk,  
CB9 8QP**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 12004:2007+A1:2012**

The notified body **MATERIALPRUFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the test according to EN 12004:2007 under System 3 and issued the following.

The notified body **MATERIALPRUFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the reaction to fire.

**Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.**



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN 15651-1: 2012-12 EN 15651-3: 2012-12 EN 15651-4: 2012-12
Resistance to flow:	$\leq 3$ mm	
Loss of volume:	$\leq 10$ %	
Tensile properties at maintained extension:	Passed (NF)	
Tear resistance:	Passed (NF)	
Tensile properties: 1) Secant modulus At +23°C: At -30°C:	$\geq 0.4$ MPa $\leq 0.9$ MPa	
Tensile properties at maintained extension in cold climate at -30°C	Passed (NF)	
Adhesion/cohesion at maintained extension after water immersion at 23°C	Passed (NF)	
Microbiological Growth:	0	
Durability:	Passed	
Release of dangerous substances	See SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ian Smith  
Laboratory Manager

Haverhill 19/10/2015