



SAFETY DATA SHEET
ARDEX AF 625

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ARDEX AF 625

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Ardex UK Limited
Homefield Road
Haverhill
Suffolk
CB9 8QP
01440 714939

Contact person safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 870 190 6777 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

Human health Irritating to eyes.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical The product is highly flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word

Danger

ARDEX AF 625

Hazard statements	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains ROSIN. May produce an allergic reaction.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243 Take action to prevent static discharges. P261 Avoid breathing vapour/ spray. P273 Avoid release to the environment. P403+P233 Store in a well-ventilated place. Keep container tightly closed.
Contains	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene, ACETONE, BUTANONE, ETHYL ACETATE
Supplementary precautionary statements	P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P391 Collect spillage. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene	20-35%
CAS number: —	EC number: 920-750-0
Classification	
Flam. Liq. 2 - H225	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

ARDEX AF 625

ACETONE	10-20%
CAS number: 67-64-1	EC number: 200-662-2
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
BUTANONE	10-20%
CAS number: 78-93-3	EC number: 201-159-0
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
ETHYL ACETATE	10-20%
CAS number: 141-78-6	EC number: 205-500-4
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
XYLENE	<1%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	
ROSIN	<0.4%
CAS number: 8050-09-7	EC number: 232-475-7
Classification	
Skin Sens. 1 - H317	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives. Toluene content = 0.0003%

SECTION 4: First aid measures

4.1. Description of first aid measures

ARDEX AF 625

General information	Move affected person to fresh air at once. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air at once. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
Specific treatments	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Heating may generate flammable vapours. The product is highly flammable. Vapours may form explosive mixtures with air. Vapours may accumulate on the floor and in low-lying areas.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Irritating gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO ₂). Hydrogen chloride (HCl).

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Ventilate closed spaces before entering them. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.
Special protective equipment for firefighters	Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

ARDEX AF 625

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.
For non-emergency personnel	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
For emergency responders	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with sand or other inert absorbent.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Keep away from heat, sparks and open flame. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid inhalation of vapours/spray and contact with skin and eyes.
Advice on general occupational hygiene	Wash promptly with soap and water if skin becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store at temperatures between 5°C and 25°C.
Storage class	Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Adhesive.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics <0.1% benzene

Long-term exposure limit (8-hour TWA): WEL 200 ppm 1,000 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTANONE

ARDEX AF 625

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

ROSIN

Long-term exposure limit (8-hour TWA): WEL 0.05 mg/m³

Short-term exposure limit (15-minute): WEL 0.15 mg/m³

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

FORMALDEHYDE ...%

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): WEL 2 ppm 2.5 mg/m³

WEL = Workplace Exposure Limit

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene**DNEL**

Consumer - Oral; Long term systematic effects: 699 mg/kg/day
 Consumer - Dermal; Long term systematic effects: 699 mg/kg/day
 Industry - Dermal; Long term systematic effects: 773 mg/kg/day
 Consumer - Inhalation; Long term systematic effects: 608 mg/m³
 Industry - Inhalation; Long term systematic effects: 2035 mg/m³

ACETONE (CAS: 67-64-1)**Ingredient comments**

WEL = Workplace Exposure Limits

DNEL

Industry - Dermal; Short term systematic effects: 186 mg/m³
 Industry - Inhalation; Short term local effects: 2420 mg/m³
 Industry - Inhalation; Long term systematic effects: 1210 mg/m³
 Consumer - Dermal; Long term systematic effects: 62 mg/kg/day
 Consumer - Inhalation; Long term systematic effects: 200 mg/m³
 Consumer - Oral; Long term systematic effects: 62 mg/m³
 Industry - Dermal; Long term systematic effects: 186 mg/kg/day

PNEC

Fresh water; 10.6 mg/l
 Marine water; 1.06 mg/l
 Sediment (Freshwater); 30.4 mg/kg
 Sediment (Marinewater); 3.04 mg/kg
 Soil; 29.5 mg/kg
 STP; 100 mg/l

BUTANONE (CAS: 78-93-3)

ARDEX AF 625

DNEL Consumer - Oral; Long term systematic effects: 31 mg/kg/day
Consumer - Dermal; Long term systematic effects: 412 mg/kg/day
Industry - Dermal; Long term systematic effects: 1161 mg/kg/day
Consumer - Inhalation; Long term systematic effects: 106 mg/m³
Industry - Inhalation; Long term systematic effects: 600 mg/m³

PNEC Fresh water; 55.8 mg/l
Marine water; 55.8 mg/l
Intermittent release; 55.8 mg/l
STP; 709 mg/l
Sediment (Marinewater); 284.7 mg/kg
Soil; 22.5 mg/kg
Sediment (Freshwater); 284.7 mg/kg

ETHYL ACETATE (CAS: 141-78-6)

DNEL Industry - Inhalation; Short term systematic effects: 1468 mg/m³
Industry - Inhalation; Short term local effects: 1468 mg/m³
Consumer - Inhalation; Short term systematic effects: 734 mg/m³
Consumer - Inhalation; Short term local effects: 734 mg/m³
Industry - Inhalation; Long term local effects: 734 mg/m³
Industry - Dermal; Long term systematic effects: 63 mg/kg/day
Industry - Inhalation; Long term systematic effects: 734 mg/m³
Consumer - Dermal; Long term systematic effects: 37 mg/kg/day
Consumer - Inhalation; Long term systematic effects: 367 mg/m³

PNEC Fresh water; 0.26 mg/l
Intermittent release; 1.65 mg/l
Sediment (Freshwater); 1.25 mg/kg
sediment (Marinewater); 0.125 mg/kg
Soil; 0.24 mg/kg
STP; 650 mg/l

XYLENE (CAS: 1330-20-7)

DNEL Consumer - Dermal; Long term systematic effects: 108 mg/kg/day
Industry - Dermal; Long term systematic effects: 180 mg/kg/day
Consumer - Inhalation; Short term local effects: 174 mg/m³
Consumer - Inhalation; Short term systematic effects: 174 mg/m³
Industry - Inhalation; Short term systematic effects: 289 mg/m³
Industry - Inhalation; Short term local effects: 289 mg/m³
Consumer - Inhalation; Long term systematic effects: 14.8 mg/m³
Industry - Inhalation; Long term systematic effects: 77 mg/m³

PNEC Fresh water; 0.327 mg/l
Soil; 2.31 mg/kg

TOLUENE (CAS: 108-88-3)

ARDEX AF 625

DNEL	Consumer - Oral; Long term systematic effects: 8.13 mg/m ³ Industry - Dermal; Long term systematic effects: 384 mg/kg/day Consumer - Inhalation; Short term local effects: 226 mg/m ³ Consumer - Inhalation; Short term systematic effects: 226 mg/m ³ Industry - Inhalation; Short term systematic effects: 384 mg/m ³ Industry - Inhalation; Short term local effects: 384 mg/m ³ Industry - Inhalation; Long term local effects: 192 mg/m ³ Consumer - Inhalation; Long term systematic effects: 56.5 mg/m ³ Industry - Inhalation; Long term systematic effects: 192 mg/m ³
PNEC	Fresh water; 0.68 mg/l Sediment (Freshwater); 16.39 mg/kg STP; 13.61 mg/l Soil; 2.89 mg/kg

ETHYLBENZENE (CAS: 100-41-4)

DNEL	Workers - Inhalation; Short term local effects: 293 mg/m ³
PNEC	- Marine water; 0.01 mg/l - Intermittent release; 0.1 mg/l - Sediment (Marinewater); 1.37 mg/l

Paratertiarybutylphenol (CAS: 98-54-4)

PNEC	Soil; 0.324 mg/kg Fresh water; 0.01 mg/l Sediment (Freshwater); 0.975 mg/l Sediment (Marinewater); 0.0975 mg/l
-------------	---

8.2. Exposure controls**Protective equipment****Appropriate engineering controls**

Provide adequate ventilation. Avoid inhalation of vapours. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Eye/face protection

Wear chemical splash goggles. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Nitrile rubber. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 6 hours. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. When used with mixtures, the protection time of gloves cannot be accurately estimated.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

ARDEX AF 625

Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
Thermal hazards	Contact with hot product can cause serious thermal burns.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Organic solvents.
Odour threshold	Not determined.
pH	Not available.
Melting point	Not applicable.
Flash point	-7°C Closed cup.
Evaporation rate	Not available.
Evaporation factor	Not determined.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 13 Lower flammable/explosive limit: 0.9
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.88 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	5500-6500 cP @ 20°C
Explosive properties	Not determined.
Oxidising properties	Not determined.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Refractive index	Not applicable.
-------------------------	-----------------

ARDEX AF 625

Particle size	Not available.
Molecular weight	Not applicable.
Saturation concentration	Not available.
Critical temperature	Not determined.
Volatile organic compound	This product contains a maximum VOC content of 633 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride (HCl).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Not determined.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not determined.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Human skin model test Not determined.

Extreme pH Not determined.

Serious eye damage/irritation

Serious eye damage/irritation Not determined.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause drowsiness and dizziness.

Ingestion

May cause stomach pain or vomiting.

ARDEX AF 625

Skin contact	Irritating to skin.
Eye contact	Causes serious eye irritation.
Route of exposure	Inhalation Skin absorption

Toxicological information on ingredients.**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 5,850.0

Species Rat

ATE oral (mg/kg) 5,850.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,000.0

Species Rabbit

ATE dermal (mg/kg) 3,000.0

ACETONE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,400.0

Species Rabbit

ATE dermal (mg/kg) 7,400.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 76.0

Species Rat

ATE inhalation (vapours mg/l) 76.0

BUTANONE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,193.0

Species Rat

ARDEX AF 625

ATE oral (mg/kg) 2,193.0

Acute toxicity - dermalAcute toxicity dermal (LD₅₀ mg/kg) 5,050.0

Species Rabbit

ATE dermal (mg/kg) 5,050.0

Acute toxicity - inhalationAcute toxicity inhalation (LC₅₀ vapours mg/l) 5,000.0

Species Rat

ATE inhalation (vapours mg/l) 5,000.0

ETHYL ACETATE**Acute toxicity - oral**Acute toxicity oral (LD₅₀ mg/kg) 4,100.0

Species Mouse

ATE oral (mg/kg) 4,100.0

Acute toxicity - dermalAcute toxicity dermal (LD₅₀ mg/kg) 2,005.0

Species Rabbit

ATE dermal (mg/kg) 2,005.0

Acute toxicity - inhalationAcute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Reproductive toxicity

Reproductive toxicity - fertility - NOAEL 16000 ppm, Inhalation, Rat P

Reproductive toxicity - development - NOAEL: 20000 ppm, Inhalation, Rat

XYLENE**Acute toxicity - oral**

ARDEX AF 625

Acute toxicity oral (LD₅₀ mg/kg) 4,300.0

Species Rat

Notes (oral LD₅₀)

ATE oral (mg/kg) 4,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 10.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

Paratertiarybutylphenol**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 5,660.0

Species Rat

ATE oral (mg/kg) 5,660.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,100.0

Species Rabbit

ATE dermal (mg/kg) 4,100.0

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment if discharged into watercourses. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity**Acute aquatic toxicity**

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

ARDEX AF 625

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

Ecological information on ingredients.**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene****Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: 1-10 mg/l, Fish
NOEC, 0.01 : 0.1 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 10-100 mg/l, Daphnia magna

Acute toxicity - microorganisms IC₅₀, : 1-10 mg/l, Activated sludge
NOEC, 0.01 : 0.1 mg/l, Activated sludge

ACETONE**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)
LC₅₀, 96 hours: >100 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 8800 mg/l, Daphnia magna

Acute toxicity - aquatic plants NOEC, 96 hours: 430 mg/l, Freshwater algae
IC₅₀, 72 hours: >100 mg/l, Algae

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 28 days: 10-<100 mg/l, Freshwater invertebrates

BUTANONE**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: 2993 mg/l, Pimephales promelas (Fat-head Minnow)
LC₅₀, 48 hours: > 100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 308 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 2029 , Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC₅₀, 96 hours: > 50 mg/l, Activated sludge

ETHYL ACETATE

ARDEX AF 625

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow) NOEC, 192 hours: > 9.65 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 610 mg/l, Daphnia magna NOEC, 192 hours: 2.4 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 48 hours: 5600 mg/l, Freshwater algae

XYLENE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 8.9 - 16.4 mg/l, Pimephales promelas (Fat-head Minnow) EC ₅₀ , 96 hours: 86 mg/l, Leuciscus idus (Golden orfe)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3.2 - 9.5 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 48 hours: 1 - 10 mg/l, Scenedesmus subspicatus

Paratertiarybutylphenol

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: > 4.71 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: > 3.5 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be slowly biodegradable.

Phototransformation Not relevant.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

Ecological information on ingredients.

ACETONE

Persistence and degradability	The product is readily biodegradable.
Biodegradation	- Degradation 91%: 28 days
Biological oxygen demand	1.9 g O ₂ /g substance
Chemical oxygen demand	2.1 g O ₂ /g substance

BUTANONE

Persistence and degradability The product is biodegradable.

ARDEX AF 625

Biodegradation Water - Degradation (%) 98: 28 days readily biodegradable

ETHYL ACETATE

Persistence and degradability The product is readily biodegradable.

Biodegradation - Degradation 79%: 20 days

XYLENE

Biodegradation Water - Degradation 60%: > 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

ACETONE

Bioaccumulative potential The product is not bioaccumulating. BCF: < 10, will not accumulate

BUTANONE

Bioaccumulative potential The product is not bioaccumulating.

ETHYL ACETATE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating. BCF: 30, Leuciscus idus (Golden Orfe) readily biodegradeable

Partition coefficient log Pow: 0.73

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

Ecological information on ingredients.

BUTANONE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

ETHYL ACETATE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Water - Koc: 1.43 @ 25°C

ARDEX AF 625

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

ACETONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

BUTANONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

ETHYL ACETATE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

XYLENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste liquid components should be suitable for incineration at an approved facility.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (ADN) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES (CONTAINS Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene)

Proper shipping name (IMDG) ADHESIVES (CONTAINS Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene)

Proper shipping name (ICAO) ADHESIVES (CONTAINS Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene)

ARDEX AF 625

Proper shipping name (ADN) ADHESIVES (CONTAINS Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics<0.1%benzene)

14.3. Transport hazard class(es)

ADR/RID class 3
 ADR/RID label 3
 IMDG class 3
 ICAO class/division 3

Transport labels**14.4. Packing group**

ADR/RID packing group II
 IMDG packing group II
 ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

**14.6. Special precautions for user**

EmS F-E, S-D
 Emergency Action Code ·3YE
 Hazard Identification Number (ADR/RID) 33
 Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations Control of Pollution Act 1974.
 Control of Substances Hazardous to Health Regulations 2002 (as amended).
 Health and Safety at Work etc. Act 1974 (as amended).
 EH40/2005 Workplace exposure limits.

ARDEX AF 625

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Safety Data Sheets for Substances and Preparations.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	<p>ATE: Acute Toxicity Estimate.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>GHS: Globally Harmonized System.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>Kow: Octanol-water partition coefficient.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>PNEC: Predicted No Effect Concentration.</p> <p>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>SVHC: Substances of Very High Concern.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p> <p>IARC: International Agency for Research on Cancer.</p> <p>MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.</p> <p>cATpE: Converted Acute Toxicity Point Estimate.</p> <p>BCF: Bioconcentration Factor.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>LOAEC: Lowest Observed Adverse Effect Concentration.</p> <p>LOAEL: Lowest Observed Adverse Effect Level.</p> <p>NOAEC: No Observed Adverse Effect Concentration.</p> <p>NOAEL: No Observed Adverse Effect Level.</p> <p>NOEC: No Observed Effect Concentration.</p> <p>LOEC: Lowest Observed Effect Concentration.</p> <p>DMEL: Derived Minimal Effect Level.</p> <p>UN: United Nations.</p> <p>IBC: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code).</p>
---	--

ARDEX AF 625

Issued by	Research and Development Manager
Revision date	20/07/2018
SDS number	20325
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains ROSIN. May produce an allergic reaction.