



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ARDEX WA Resin
Product code : 60401;60413; 60418; 60412; 60414

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Construction materials
Use of the substance/mixture : Grouting Compounds
Tiling

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Ardex UK Limited

Homefield Road

CB9 8QP Haverhill Suffolk

T 01440 714939 - F 01440 716667

E-mail address of competent person responsible for the SDS : safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 870 190 6777
24 hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) :

Warning

Hazardous ingredients :

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; 2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane; bisphenol-F-epichlorhydrin epoxy resin

Hazard statements (CLP) :

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P280 - Wear eye protection, protective clothing.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

EUH-statements	: contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Extra phrases	: EUH205 - Contains epoxy constituents. May produce an allergic reaction. : Dispose of contents/container in accordance with regional/national/international/local regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
quartz, conc respirable crystalline silica<1 % substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	> 40	Not classified
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	> 16 - < 22	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	> 2,5 - < 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
bisphenol-F-epichlorhydrin epoxy resin	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	> 3 - < 6	Skin Sens. 1, H317 Skin Irrit. 2, H315 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	(5 ≤C ≤ 100) Eye Irrit. 2, H319 (5 ≤C ≤ 100) Skin Irrit. 2, H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move to fresh air. If symptoms persist call a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None reasonably foreseeable.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Severe eye irritation.
Symptoms/effects after ingestion	: Irritating to the respiratory system and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing media allowed.
Unsuitable extinguishing media	: None.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Heat may cause pressure rise with explosion of tanks/drums.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide.

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

5.3. Advice for firefighters

- Precautionary measures fire : Evacuate area.
- Firefighting instructions : Contain the extinguishing fluids by bunding. Do not allow run-off from fire-fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear personal protective equipment.
- Emergency procedures : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Protective gloves. Safety glasses. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Do not allow to enter drains or water courses.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

- See Heading 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : See Heading 8. When mixing the components: Please note the safety data sheet for the second component.
- Precautions for safe handling : Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only in well ventilated areas. Do not leave mixed material in the container - hardening can lead to strong heat development.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Provide local exhaust or general room ventilation.
- Storage conditions : Keep container closed when not in use. Store in original container.
- Incompatible products : Oxidizing agent. Strong bases. Strong acids.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

quartz, conc respirable crystalline silica<1 % (14808-60-7)		
EU	Local name	Silica crystalline (Quartz)
EU	IOEL TWA	0.1 mg/m ³ (Respirable fraction)
EU	Notes	(Year of adoption 2003)
United Kingdom	WEL TWA (OEL TWA) [1]	0.1 mg/m ³

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1 mg/kg bw/day
Long-term - systemic effects, inhalation	3.6 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.5 mg/kg bw/day
Long-term - systemic effects, inhalation	0.87 mg/m ³
Long-term - systemic effects, dermal	0.5 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	0.106 mg/l

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
PNEC aqua (marine water)	0.011 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	307.16 mg/kg dwt
PNEC sediment (marine water)	30.72 mg/kg dwt
PNEC (Soil)	
PNEC soil	1.234 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
DNEL/DMEL (Workers)	
Acute - local effects, dermal	8.3 µg/cm²
Long-term - systemic effects, dermal	104.15 mg/kg bw/day
Long-term - systemic effects, inhalation	29.39 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	6.25 mg/kg bw/day
Long-term - systemic effects, inhalation	8.7 mg/m³
Long-term - systemic effects, dermal	62.5 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	0.003 mg/l
PNEC aqua (marine water)	0.0003 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.294 mg/kg dwt
PNEC sediment (marine water)	0.0294 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.237 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Respiratory protection not required in normal conditions. In case of splash hazard: safety glasses. Protective goggles. Gloves.

Hand protection:

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	1 (> 10 minutes)	0,1		
Reusable gloves	Nitrile rubber (NBR), Butyl rubber	6 (> 480 minutes)	0,5		EN ISO 374

Eye protection:

Type	Field of application	Characteristics	Standard
Safety goggles	Safety goggles recommended during refilling. Wear security glasses which protect from splashes	With side shields, Plastic	

Skin and body protection:

Type	Standard
Safety shoes, Skin protection appropriate to the conditions of use should be provided, Long sleeved protective clothing	

Respiratory protection:

Device	Filter type	Condition	Standard
Gas filters	A1	Vapour protection	



ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Various.
Odour	: Amine-like.
Odour threshold	: No data available
pH	: 8 – 9
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 200 °C
Flash point	: > 100 °C
Auto-ignition temperature	: > 350 °C
Decomposition temperature	: > 200 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.1 – 1.3 g/cm ³
Solubility	: Forms emulsion in presence of water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
LD50 oral rat	26800 mg/kg bodyweight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 4000 mg/kg
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal)

Skin corrosion/irritation : Causes skin irritation.
pH: 8 – 9

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Serious eye damage/irritation	: Causes serious eye irritation. pH: 8 – 9
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
LC50 - Fish [1]	1.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Weight of evidence)
EC50 - Crustacea [1]	3.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Weight of evidence, GLP)
EC50 72h - Algae [1]	> 1.8 mg/l (Equivalent or similar to OECD 201, Selenastrum capricornutum, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
Persistence and degradability	Readily biodegradable in water.
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
Persistence and degradability	Biodegradability in water: no data available.
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
Persistence and degradability	Not readily biodegradable in water.
quartz, conc respirable crystalline silica<1 % (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
BCF - Fish [1]	160 – 263 (BCFWIN, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	3.77 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
Bioaccumulative potential	Not bioaccumulative.
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
BCF - Fish [1]	150 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	2.7 – 3.6 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
quartz, conc respirable crystalline silica<1 % (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
Partition coefficient n-octanol/water (Log Koc)	> 5.63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	
Partition coefficient n-octanol/water (Log Koc)	3.65 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
quartz, conc respirable crystalline silica<1 % (14808-60-7)	
Surface tension	No data available in the literature

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

quartz, conc respirable crystalline silica <1 % (14808-60-7)	
Ecology - soil	Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Component	
quartz, conc respirable crystalline silica <1 % (14808-60-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
bisphenol-F-epichlorhydrin epoxy resin (9003-36-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available





SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: M6
Limited quantities (ADR)	: 5I

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Excepted quantities (ADR) : E1
Transport category (ADR) : 3
Orange plates :



Tunnel restriction code (ADR) : -
EAC code : •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA max net quantity (IATA) : 450L

- Inland waterway transport

Classification code (ADN) : M6
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1

- Rail transport

Classification code (RID) : M6
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Transport category (RID) : 3

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

ARDEX WA Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.