

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ARDEX R 5 E PART A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses 2 Part Epoxy Primer

1.3. Details of the supplier of the safety data sheet

Supplier Ardex UK Limited

Homefield Road

Haverhill Suffolk CB9 8QP 01440 714939

Contact person safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 870 190 6777 (24 hours)

National emergency telephone ROI:- +353 (0)1 809 2166 (available 8am-10pm, 7 days)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms





Signal word Warning

Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

ARDEX R 5 E PART A

Precautionary statements P102 Keep out of reach of children.

P261 Avoid breathing vapour/ spray.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains EPOXY RESIN (Number average MW <= 700), BISPHENOL F EPICHLOROHYDRIN RESIN,

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700)

60-100%

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

BISPHENOL F EPICHLOROHYDRIN RESIN

10-30%

CAS number: 28064-14-4

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

10-30%

CAS number: 68609-97-2

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Instantly remove any clothing soiled by the product

Inhalation Remove person to fresh air and keep comfortable for breathing. Get medical attention if any

discomfort continues.

Ingestion Get medical attention immediately.

ARDEX R 5 E PART A

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if

any discomfort continues.

Eye contact Rinse immediately with plenty of water. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information No specific recommendations.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Avoid inhalation of vapours and contact with skin and

eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up When handling waste, the safety precautions applying to handling of the product should be

considered. Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not discharge

into drains or watercourses or onto the ground.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

skin and eyes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

ARDEX R 5 E PART A

Storage precautions Store in tightly-closed, original container. Keep away from food, drink and animal feeding

stuffs.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL Professional - Dermal; Short term systemic effects: 8.3 mg/kg/day

Professional - Inhalation; Short term systemic effects: 12.3 mg/m³ Professional - Dermal; Long term systemic effects: 8.3 mg/kg/day Professional - Inhalation; Long term systemic effects: 12.3 mg/m³ Consumer - Dermal; Short term systemic effects: 3.6 mg/kg/day Consumer - Inhalation; Short term systemic effects: 0.75 mg/m³ Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day Consumer - Dermal; Long term systemic effects: 3.6 mg/kg/day

General population - Inhalation; Long term systemic effects: 0.75 mg/m³ General population - Oral; Long term systemic effects: 0.75 mg/kg/day

PNEC Fresh water; 0.003 mg/l

marine water; 0.0003 mg/l

BISPHENOL F EPICHLOROHYDRIN RESIN (CAS: 28064-14-4)

DNEL Workers - Dermal; Short term : 29.39 mg/m³

Workers - Dermal; Short term: 104.15 mg/kg/day

PNEC Fresh water; 0.003 mg/l

marine water; 0.0003 mg/l

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS (CAS: 68609-97-2)

DNEL Workers - Dermal; Short term : 3.9 mg/kg/day

Workers - Inhalation; Short term: 13.8 mg/m³

PNEC Fresh water; 0.0072 mg/l

marine water; 0.00072 mg/l

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection Wear protective gloves.

ARDEX R 5 E PART A

Other skin and body

protection

No specific requirements are anticipated under normal conditions of use.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory

protection complying with an approved standard should be worn if a risk assessment indicates

inhalation of contaminants is possible.

Thermal hazards Not applicable.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Yellowish.

Odour Characteristic.

Odour threshold Not applicable.

pH Not applicable.

Melting point Not determined.

Initial boiling point and range > 200°C

Flash point > 100°C

Evaporation rate Not applicable.

Evaporation factor Not applicable.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Not applicable.

Other flammability Not applicable.

Vapour pressure Not applicable.

Vapour density Not applicable.

Relative density 1.12 @ 23°C

Bulk density Not applicable.

Solubility(ies) Immiscible with water.

Partition coefficient Not applicable.

Auto-ignition temperature Not applicable.

Decomposition Temperature Not applicable.

Viscosity Not applicable.

Explosive properties Not applicable.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not applicable.

ARDEX R 5 E PART A

Comments Information declared as "Not available" or "Not applicable" is not considered to be relevant to

the implementation of the proper control measures.

9.2. Other information

Other information Not applicable.

Refractive index Not applicable.

Particle size Not applicable.

Molecular weight Not applicable.

Volatility Not applicable.

Saturation concentration Not applicable.

Critical temperature Not applicable.

Volatile organic compound Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Toxic gases and vapours.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

11,400.0

Species Rat

ATE oral (mg/kg) 11,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 20,000.0

mg/kg)

ARDEX R 5 E PART A

Species Rabbit

ATE dermal (mg/kg) 20,000.0

.

Skin contact Slightly irritating.

BISPHENOL F EPICHLOROHYDRIN RESIN

.

Inhalation No significant hazard at normal ambient temperatures. Heating may generate the

following products: Harmful gases or vapours.

Ingestion Harmful if swallowed.

Skin contact Slightly irritating. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

26,800.0

Species Rat

ATE oral (mg/kg) 26,800.0

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1.3 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 2.1 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

LC₅₀, 72 hours: 11 mg/l, Algae

Chronic aquatic toxicity

Chronic toxicity - fish early LC₅₀, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.3 mg/l, Daphnia magna

BISPHENOL F EPICHLOROHYDRIN RESIN

Toxicity Toxic to aquatic life.

Acute aquatic toxicity

Acute toxicity - fish EC₅₀, 96 hour: 2.54 mg/l, Leuciscus idus (Golden orfe)

ARDEX R 5 E PART A

Acute toxicity - aquatic

invertebrates

LC₅₀, 48 hour: 2.55 mg/l, Daphnia magna

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1800 mg/l, Lepomis macrochirus (Bluegill)

LC₈₀, 96 hours: >5000 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 7.2 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 844 mg/l, Selenastrum capricornutum

12.2. Persistence and degradability

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Persistence and

degradability

Not expected to be readily biodegradable.

BISPHENOL F EPICHLOROHYDRIN RESIN

Persistence and

degradability

Not expected to be readily biodegradable.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

The substance is readily biodegradable. Biodegradation

12.3. Bioaccumulative potential

Partition coefficient Not applicable.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Bioaccumulative potential BCF: 3-31,

Partition coefficient Partition coefficient, n-octanol/water log Pow 3.2 estimated.

BISPHENOL F EPICHLOROHYDRIN RESIN

Bioaccumulative potential BCF: 100-3000.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Bioaccumulative potential Potentially bioaccumulating. BCF: ~ 160-263, Estimated value., Fish

Partition coefficient Partition coefficient, n-octanol/water log Pow 3.77: OEECD 107 test: shake flask

method.

12.4. Mobility in soil

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

ARDEX R 5 E PART A

Adsorption/desorption coefficient

Expected to have a low potential for adsorption.

BISPHENOL F EPICHLOROHYDRIN RESIN

Adsorption/desorption coefficient

Not available.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Mobility Not considered mobile.

Adsorption/desorption

coefficient

Koc >5000 OECD 121: HPLC method.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

BISPHENOL F EPICHLOROHYDRIN RESIN

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used sacks in accordance with local regulations.

Disposal methods For disposal, local regulations issued by the authorities must be observed. Dispose of liquid

components at a suitable incineration plant. After curing, the product can be disposed of with

household waste.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082
UN No. (ADN) 3082

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW <= 700), BISPHENOL F EPICHLOROHYDRIN RESIN)

ARDEX R 5 E PART A

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY

RESIN (Number average MW <= 700), BISPHENOL F EPICHLOROHYDRIN RESIN)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY

RESIN (Number average MW <= 700), BISPHENOL F EPICHLOROHYDRIN RESIN)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY Proper shipping name (ADN)

RESIN (Number average MW <= 700), BISPHENOL F EPICHLOROHYDRIN RESIN)

14.3. Transport hazard class(es)

ADR/RID class

ADR/RID classification code M6

ADR/RID label 9

IMDG class 9

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group Ш

IMDG packing group Ш

ICAO packing group Ш

ADN packing group Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A. S-F

3 ADR transport category

Emergency Action Code •3Z

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

90

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

ARDEX R 5 E PART A

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued byUK Regulatory and Product Compliance Officer

Revision date 07/09/2022

SDS number 20400

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.