



SAFETY DATA SHEET ARDEX WPM 200 Part A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ARDEX WPM 200 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses For professional use only. Primer. Damp Proof Membrane. Waterproof coating.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Ardex UK Limited
Homefield Road
Haverhill
Suffolk
CB9 8QP
01440 714939

Contact person safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 870 190 6777 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317


Environmental hazards Aquatic Chronic 2 - H411

Human health Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

ARDEX WPM 200 Part A

Precautionary statements	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P313 Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with local regulations.</p>
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	EPOXY RESIN (Number average MW <= 700), OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS, BISPHENOL F EPICHLOROHYDRIN RESIN

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700)	10-30%
CAS number: 25068-38-6 EC number: 500-033-5	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS	10-30%
CAS number: 68609-97-2	
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
BISPHENOL F EPICHLOROHYDRIN RESIN	1-5%
CAS number: 28064-14-4	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
DI-ISOBUTYL KETONE	<1%
CAS number: 108-83-8 EC number: 203-620-1	
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335	

ARDEX WPM 200 Part A

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA	<1%
CAS number: 64742-95-6 EC number: 265-199-0	
Classification Flam. Liq. 1 - H224 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	No further information available.
Inhalation	This product is strongly irritating.
Ingestion	Nausea, vomiting.
Skin contact	The product contains a sensitising substance.
Eye contact	Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
Hazardous combustion products	Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting	Fight fire from safe distance or protected location.
---	--

ARDEX WPM 200 Part A

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Clean contaminated objects and areas thoroughly, observing environmental regulations.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DI-ISOBUTYL KETONE

Long-term exposure limit (8-hour TWA): WEL 25 ppm 148 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

ARDEX WPM 200 Part A

DNEL	Professional - Dermal; Short term systemic effects: 8.3 mg/kg/day
	Professional - Inhalation; Short term systemic effects: 12.3 mg/m ³
	Professional - Dermal; Long term systemic effects: 8.3 mg/kg/day
	Professional - Inhalation; Long term systemic effects: 12.3 mg/m ³
	Consumer - Dermal; Short term systemic effects: 3.6 mg/kg/day
	Consumer - Inhalation; Short term systemic effects: 0.75 mg/m ³
	Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 3.6 mg/kg/day
	General population - Inhalation; Long term systemic effects: 0.75 mg/m ³
General population - Oral; Long term systemic effects: 0.75 mg/kg/day	

OXIRANE, MONO [(C12-14- ALKYL)OXY]METHYL] DERIVS (CAS: 68609-97-2)

DNEL	Workers - Dermal; Short term : 3.9 mg/kg/day
	Workers - Inhalation; Short term : 13.8 mg/m ³

BISPHENOL F EPICHLOROHYDRIN RESIN (CAS: 28064-14-4)

DNEL	Workers - Dermal; Short term : 29.39 mg/m ³
	Workers - Dermal; Short term : 104.15 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). Thickness: ≥ 0.1 mm The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. It is recommended to use respiratory equipment with combination filter, type A2/P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured paste.
Colour	Various colours.
Odour	Characteristic.
pH	pH (concentrated solution): 8-9
Initial boiling point and range	200°C

ARDEX WPM 200 Part A

Flash point	>100°C
Relative density	~ 1.3
Solubility(ies)	Forms an emulsion with water.
Auto-ignition temperature	>350°C

9.2. Other information

Other information	No information required.
-------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
------------------------------------	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid contact with acids. Strong oxidising agents.
---------------------	--

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong alkalis.
--------------------	-------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	No significant hazard at normal ambient temperatures. Heating may generate the following products: Toxic gases or vapours.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	May cause sensitisation by skin contact.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	May cause respiratory system irritation. May cause sensitisation by skin contact. The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
Route of exposure	Inhalation Skin absorption Skin and/or eye contact
Target organs	No specific target organs known.

Toxicological information on ingredients.

EPOXY RESIN (Number average MW ≤ 700)

Acute toxicity - oral

ARDEX WPM 200 Part A

Acute toxicity oral (LD₅₀ mg/kg) 11,400.0

Species Rat

ATE oral (mg/kg) 11,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

Skin contact Slightly irritating.

OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 26,800.0

Species Rat

ATE oral (mg/kg) 26,800.0

BISPHENOL F EPICHLOROHYDRIN RESIN

Inhalation No significant hazard at normal ambient temperatures. Heating may generate the following products: Harmful gases or vapours.

Ingestion Harmful if swallowed.

Skin contact Slightly irritating. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity**Ecological information on ingredients.****EPOXY RESIN (Number average MW ≤ 700)****Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: 1.3 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 2.1 mg/l, Daphnia magna

Acute toxicity - aquatic plants LC₅₀, 72 hours: 11 mg/l, Algae

Chronic aquatic toxicity

Chronic toxicity - fish early life stage LC₅₀, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)

ARDEX WPM 200 Part A

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.3 mg/l, Daphnia magna

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1800 mg/l, Lepomis macrochirus (Bluegill)
LC₈₀, 96 hours: >5000 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7.2 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 844 mg/l, Selenastrum capricornutum

BISPHENOL F EPICHLOROHYDRIN RESIN

Toxicity Toxic to aquatic life.

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable. The product is slowly degradable.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Persistence and degradability Not expected to be readily biodegradable.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Biodegradation The substance is readily biodegradable.

BISPHENOL F EPICHLOROHYDRIN RESIN

Persistence and degradability Not expected to be readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Bioaccumulative potential BCF: 3-31,

Partition coefficient Partition coefficient, n-octanol/water log Pow 3.2 estimated.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Bioaccumulative potential Moderate potential for bioaccumulation. BCF: ~ 160-263, Fish, Estimated value.

Partition coefficient Partition coefficient, n-octanol/water log Pow 3.77: OEECD 107 test: shake flask method.

BISPHENOL F EPICHLOROHYDRIN RESIN

ARDEX WPM 200 Part A

Bioaccumulative potential BCF: 100-3000,

12.4. Mobility in soil

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Adsorption/desorption coefficient Expected to have a low potential for adsorption.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Mobility Not considered mobile.

Adsorption/desorption coefficient Koc >5000 OECD 121: HPLC method.

BISPHENOL F EPICHLOROHYDRIN RESIN

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

BISPHENOL F EPICHLOROHYDRIN RESIN

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not relevant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

ARDEX WPM 200 Part A

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW ≤ 700), BISPHENOL F EPICHLOROHYDRIN RESIN)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW ≤ 700), BISPHENOL F EPICHLOROHYDRIN RESIN)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW ≤ 700), BISPHENOL F EPICHLOROHYDRIN RESIN)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW ≤ 700), BISPHENOL F EPICHLOROHYDRIN RESIN)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

ARDEX WPM 200 Part A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data	Selected exposure, bioaccumulation and toxicology data taken from Dow and Momentive MSDSs
Revision comments	1
Issued by	Research and Development Manager
Revision date	13/04/2018
SDS number	20343
Hazard statements in full	H224 Extremely flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.