

TILE FIXING PRODUCT GUIDE

Everything
covered...

- Prepare
- Fix
- Finish
- Technical Support
& Training

GIUBAX
REWARDS



ardex.co.uk

welcome to



As an installer of quality tiling, you want a manufacturer you can trust to provide products that make your job quicker, easier and providing a high-quality finish.

At ARDEX our history goes back more than 60 years, so we've certainly seen a lot of changes! But one thing has remained the same – and that's being at the forefront of the UK professional tiling and flooring trades.


ARDEX now operates more than 50 sites across the globe, supplying premium products for wall and floor preparation and the fixing of tiles and natural stone.

We've been fortunate enough to have seen our products specified on several highly prestigious projects across the world, from the iconic 2012 London Olympics Aquatic Centre to one of the largest shopping malls in the world in Dubai.



At ARDEX we are always working hard to promote professionalism, technical standards and best practice within the tiling trade. That is why we are active members of The Tile Association and Stone Federation of Great Britain, and all our products are manufactured under a quality system certified to ISO 9001, 14001 and ISO 45001. While these might seem like numbers plucked from thin air, they are actually internationally recognised manufacturing standards that help us produce solutions that you can trust.

This guide contains information on the essential ARDEX products required by the modern, professional tile fixer. For further information on the full ARDEX range, visit www.ardex.co.uk



TTA Winners 2014, 2015 and 2017



Contents

GivBax Rewards 4-5

Best Practice Tiling Guide 6-7

Natural Stone Fixing Guide 8-9

PREPARE 10-31

Priming 10-12

Repairing & Ramp Forming 13-16

Screeding 17-19

Wall Renders, Waterproofing & DPM 20-25

Levelling 26-29

Uncoupling Membranes 30-31

FIX 32-49

Ready Mixed Adhesive 34-35

Flexible W & F Adhesives – Standard Setting 36-38

Flexible W & F Adhesives – Rapid Setting 39-41

Pourable Floor Adhesives 42-47

Adhesives Admix 48

Reaction Resin Adhesive 49

FINISH 50-59

Cement Based Grouts 50-52

Epoxy Grouts 53-54

Silicones 55-57

Technical Support & Training 60-61



THE APP THAT REWARDS YOUR PURCHASES WITH CASH



Scan for more info.

GIVBAX REWARDS

An ARDEX Group UK Loyalty Programme
T&C's apply. See givbax-rewards.com

WHAT IS GIVBAX REWARDS?

GivBax Rewards – from ARDEX and BAL – is the simplest, most rewarding loyalty App for professional Floorlayers and Tile Fixers.

HOW DOES IT WORK?

Simply download the App, buy your ARDEX or BAL products, scan your receipt in the App to earn points and redeem your points on great rewards – including cash! – available to withdraw from over 18,000 ATMs across the UK.

It's time to turn purchases into pounds!

SEE - SCAN - SPEND

As an easy reference guide we have included the GivBax Rewards points that each product shown in this guide will generate when purchased and uploaded. Just look out for the **yellow** box next to each product!

NOTE: GivBax Rewards points correct at date of printing.



3
POINTS

Best practice

1. EVALUATE THE SUBSTRATE

Before tiling, ask yourself, “Is the background flat enough?”. Did you know that British Standards require that variations in the floor do not exceed 3mm when measured under a 2m straight edge? To make sure your floors are in perfect level condition to tile, you can level floors with ARDITEX NA or ARDEX K 40 HB. Sometimes walls also need to be made good and flat; in this instance, you can use ARDEX AM 100.

When wall tiling, it's always best to check whether your background is strong enough. The last thing you want is backgrounds crumbling under the weight of tiles and adhesive, causing you no end of problems.

Check if your wall background will support the weight of the tiles, adhesive and grout using the table below:

Maximum weight restrictions for backgrounds

Gypsum plaster	20kg/m ²
Plasterboard and plywood	32kg/m ²
Proprietary tile backing boards	60kg/m ² *
Cement and sand render/concrete	64kg/m ²

*Refer to manufacturer guidelines for exact weight limitations

2. CONSIDER ROOM CONDITIONS

Do you waterproof your backgrounds in wet areas? Well, if you want to avoid costly failure due to water damage, you should consider using a waterproofing tanking system like ARDEX WPC to prevent water from penetrating into the background

3. PRIMING

Making sure your adhesive or levelling compound bonds to the substrate is one of the most critical aspects of tiling. Although not always essential, best practice suggests priming surfaces with ARDEX P 51 or ARDEX P 4 before laying a leveller or spreading tile adhesive. Primers help ensure adhesion on absorbent surfaces such as plaster and gypsum screeds, while on wood, they help prevent expansion.

Did you know that according to BS 5385, it is now recommended to waterproof wet areas in both domestic and commercial areas?

4. USE THE CORRECT ARDEX TILE ADHESIVE

- **Speed:** ARDEX X 77 S or ARDEX X 78 S will allow grouting to commence after just 90 minutes!
- **Stone:** Some stones are moisture sensitive, so opt for an ARDEX RAPIDRY FORMULA adhesive to prevent staining and warping. You can read our guidance notes on installing stone on p.6-7.
- **Large format tiles:** Use ARDEX Cement-Based Tile Adhesives to fix larger tiles confidently. For more coverage and a longer time to fix on walls or floors, use a MICROTEC adhesive.
- **Fixing to timber:** Wood is a challenging substrate as it can absorb moisture from its surroundings, causing warping and movement. Prime timber with ARDEX P 51 and then fix tiles with ARDEX X 7001, a RAPIDRY FORMULA adhesive that locks in the mix water and helps prevent this from happening.
- **Fixing to fibreglass, steel and PVC coverings:** These can be pretty tricky surfaces to tile to, so we would recommend using our ARDEX X 60 PU FLEX to tile direct to these problematic substrates without priming.

5. USE THE CORRECT ARDEX TILE GROUT

ARDEX-FLEX FS and ARDEX-FLEX FL are suitable for grouting most installations and are available in 35 colours to suit any tiling project. If you need an epoxy grout, use ARDEX EG 18 Plus, it combines the chemical resistance of epoxy grouts with the enhanced application properties of cement-based grouts. For moisture sensitive natural stone, use ARDEX MG to remove the risk of water staining.

6. SILICONE SEALING

ARDEX ST Silicone Sealant creates an elastic joint resistant to weather, UV radiation and commonly used cleaning chemicals. It contains fungicide and is available in transparent and 13 colours, complementing the ARDEX-FLEX Tile Grout range and providing you with that perfect finish for your tiling project.

For specific technical queries call one of our technical support team on 01440 714939.





Fixing natural stone

Natural and agglomerated stones such as granite, marble and limestone are naturally durable materials that can last a lifetime. However, like any product, problems may occur if they are not installed correctly.

BLOB FIXING



PICTURE FRAMING



The main issue with this type of installation is knowing whether the stone is moisture sensitive or not and then choosing the correct products to fix it. In most instances, natural stone tiles will not have a sensitivity to moisture, and non-specialist products can be used with confidence; however, using such products to fix moisture sensitive stone can lead to disastrous results – which might cost you time and money to repair – and we don't want that!

The problem with most traditional adhesives and grouts is that they contain a lot of water. While this might be good for ease of use, it can cause problems when fixing natural stone. This moisture can travel up into the stone during the fixing and grouting process and cause discolouration, staining, and even warping.

For tile fixers installing moisture sensitive natural or agglomerated stones, or for those unsure what they are fixing, ARDEX has developed several products specifically to eliminate these potential problems. This means you will be confident that your installation will look great and last the test of time.

ARDEX natural stone products incorporate our unique RAPIDRY FORMULA technology and 'lock' the mix water within the mortar, virtually eliminating the risk of water staining and warping. Always ensure you apply tiles onto a solid bed of adhesive.

Our specialist range:

- Prevents water damage and allows confident fixing of moisture-sensitive natural and agglomerated stones
- Can fix uncalibrated natural stone
- Means floors can be walked on in the shortest time possible – great for projects that require a quick turnaround.
- Facilitates solid bed fixing

When fixing natural stone, use ARDEX Natural Stone products with RAPIDRY FORMULA Technology. Simply lookout for the logo throughout this guide.



**BEST INNOVATION:
ARDEX NATURAL
STONE RANGE**

**RAPIDRY
FORMULA**



PRIMING

JUST ONE COAT

Making sure your tile adhesives and floor levelling compounds are correctly bonding to the substrate.

ARDEX P 51

CONCENTRATED WATER-BASED PRIMER & BONDING AGENT

DESCRIPTION

A concentrated, blue, synthetic, water-based, solvent-free multi-purpose primer with a wide range of applications which, after drying, helps to inhibit the penetration of water from subsequently applied materials.



SUITABLE SUBSTRATES

Concrete, sand and cement screeds, anhydrite screeds, plaster and timber



SUITABLE FOR EXTERNAL USE OR WET AREAS

No



PACK SIZE

1kg, 5kg and 25kg bottles



COVERAGE

1kg – up to 32m² per bottle
5kg – up to 160m² per bottle
25kg – up to 800m² per bottle



45
POINTS

25kg

9
POINTS

5kg

3
POINTS

1kg

ARDEX P 4

READY MIXED RAPID DRYING PRIMER

DESCRIPTION

Solvent-free primer for internal and external use on absorbent and non-absorbent backgrounds. ARDEX P 4 produces a textured surface and helping the adhesion of cement-based tile adhesives in tile-on-tile applications.



SUITABLE SUBSTRATES

Ceramic tiles, terrazzo, concrete, cement/lime render, sand and cement screeds, levelling compounds and dispersion based paints




SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



FIX TILES AFTER

As little as 30 minutes



14
POINTS



PACK SIZE

2kg and 8kg tubs



COVERAGE

2kg – 10m² per tub
8kg – 40m² per tub

Substrate	Dilution Ratio (ARDEX P 51:water)
Wood-based sheets and boards to receive levelling compounds and cement-based tile adhesives	Undiluted
Smooth and non-porous substrates to receive levelling compounds and cement-based tile adhesives	1:½
Rough concrete floors to receive levelling compounds	1:1
Power floated concrete to receive levelling compounds	1:2
Prepared gypsum plaster walls and floors to receive cement-based tile adhesives	1:3
Porous or highly absorbent cement screeds to receive levelling compounds and repair mortars	1:5

Use ARDEX P 4 before ARDEX Cement-Based Tile Adhesives when tiling direct to existing tiles





PRIMING



REPAIRS & RAMP FORMING

ARDEX P 82

READY MIXED RAPID DRYING PRIMER

DESCRIPTION

Designed for priming smooth and impervious surfaces such as concrete, terrazzo, glazed ceramics, quarry tiles, metal and sound paint coatings. Ideal for priming ARDEX Damp Proof Membranes and for use on floors with flooring grade asphalt.

25
POINTS



SUITABLE SUBSTRATES

Terrazzo, glazed ceramics, quarry tiles and porcelain.



PACK SIZE

2kg and 6kg tubs



COVERAGE

Approximately 60m² per 6kg unit.



Use **ARDEX P 4** before **ARDEX Cement-Based Tile Adhesives** when tiling direct to existing tiles

ARDEX FA 20

FIBRE REINFORCED LEVELLING AND SMOOTHING COMPOUND

DESCRIPTION

ARDEX FA 20 is an advanced fibre reinforced smoothing and levelling compound, featuring MICROTEC technology that is designed to rapidly smooth and level new and existing substrates prior to applying a floor finish. ARDEX FA 20 can be applied to timber floors, flooring grade asphalt and existing substrates with adhesive residues. ARDEX FA 20 can normally be walked on after approximately 2 hours at 20°C.



10
POINTS



SUITABLE SUBSTRATES

Timber floors



APPLICATION THICKNESS

3-10mm and up to 20mm with suitable aggregate



POT LIFE

30 minutes



FIX TILES AFTER

Ready to receive floor coverings next day



USE WITH UNDERFLOOR HEATING

Yes



PACK SIZE

20kg bag



COVERAGE

5m² per bag at 3mm thickness



Prime floors with **ARDEX P 51** before applying



REPAIRS & RAMP FORMING



Repair mortar

Create ramps and falls and make minor, localised repairs

ARDEX A 46

RAPID SET REPAIR MORTAR

DESCRIPTION

Don't waste time with traditional sand: cement renders when making internal and external repairs to walls and floors before tiling. ARDEX A 46 saves you time when making good around pipework and other fittings, plus it is excellent for creating ramps and falls in wetrooms or repairing holes in concrete, sand and cement screeds and steps.

SUITABLE SUBSTRATES
Concrete, sand and cement screeds, brickwork, blockwork, and renders

SUITABLE FOR EXTERNAL USE OR WET AREAS
Yes

APPLICATION THICKNESS
2-50mm


POT LIFE
15 minutes

5
POINTS

11kg

3
POINTS

5kg



FIX TILES AFTER
4 hours

USE WITH UNDERFLOOR HEATING
Yes

PACK SIZE
5kg buckets & 11kg bags

COVERAGE
5kg - 1.8m² per bucket at 2mm thickness
11kg - 4m² per bag at 2mm thickness

ARDEX S 21

RAPID SETTING FLOOR TILE BEDDING MORTAR

DESCRIPTION

ARDEX S 21 is a special rapid hardening pourable bedding mortar for floor tiles in internal and external locations. It is especially suitable for fixing large tiles, ceramic and brick pavers, terrazzo tiles and natural stone etc.

SUITABLE SUBSTRATES
Suitable for dry or moist sub-floors, such as cement and sand or concrete screeds.

SUITABLE FOR EXTERNAL USE
Yes

8
POINTS



WORKING TIME
30 minutes

FIX TILES AFTER
Fix within 10 min when used as bedding mortar and tile after 3 hours if used as leveller.

USE WITH UNDERFLOOR HEATING
Yes

PACK SIZE
22kg bag

COVERAGE
Approximately 4.0m² at 3mm thick per 22kg bag

Prime floors with **ARDEX P 51** before applying





REPAIRS & RAMP FORMING



SCREEDING

ARDEX P 10 SR

RAPID HARDENING CRACK REPAIR RESIN KIT



6
POINTS

DESCRIPTION

ARDEX P 10 SR Rapid Hardening Crack Repair Resin Kit is a solvent free polymer modified 2 component silicate resin system. The kit is easy to use and includes stitching pins, mixing/dosing bottles and protective gloves. It can be used for the rapid repair of non-structural cracks, joint sealing and as a rapid hardening general-purpose adhesive.

SUITABLE FOR EXTERNAL USE OR WET AREAS

No

WORKING TIME

10 minutes

FIX TILES AFTER

40 minutes

USE WITH UNDERFLOOR HEATING

Yes

PACK SIZE

600ml kit (2 x 300ml)

COVERAGE

Each 600ml kit will repair approximately 4 linear meters.

ARDEX A 29

RAPID HARDENING CEMENT FOR INTERNAL AND EXTERNAL SCREEDS



4
POINTS

DESCRIPTION

ARDEX A 35 has been specially formulated to produce ultra-rapid drying floor screeds for internal and external locations. With 'RAPIDRY FORMULA' Technology, an ARDEX A 35 screed can be walked on just 3 hours after application and ceramic and natural stone tiles can be installed after just 24 hours irrespective of thickness. Resilient floorcoverings such as carpet, vinyl and wood can be installed after 24 hours.

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

WORKING TIME

90 minutes

FIX TILES AFTER

24 hours

USE WITH UNDERFLOOR HEATING

Yes

PACK SIZE

25kg Bag

COVERAGE

Approximately 0.27kg ARDEX A 29 cement per m² for each millimetre of screed thickness using a 1:7 mix.



SCREEDING



ARDEX A 35


ULTRA RAPID DRYING CEMENT FOR INTERNAL SCREEDS

8
POINTS

25kg

6
POINTS

MIX 25kg



DESCRIPTION

ARDEX A 35 has been specially formulated to produce ultra-rapid drying floor screeds for internal locations. With 'RAPIDRY FORMULA' Technology, an ARDEX A 35 screed can be walked on just 3 hours after application and ceramic and natural stone tiles can be installed after just 24 hours irrespective of thickness. Resilient floorcoverings such as carpet, vinyl and wood can be installed after 24 hours.

 **SUITABLE FOR EXTERNAL USE**
No

 **WALK ON**
after 3 hours

 **FIX TILES AFTER**
24 hours

 **WORKING TIME**
1 hour

 **PACK SIZE**
25kg Bag

 **COVERAGE**
Approximately 2.7m² at 25mm thick or 4.5m² at 15mm thick per bag.

 **USE WITH UNDERFLOOR HEATING**
Yes

 **APPLICATION THICKNESS**
Bonded screeds: 15mm - 40mm
Unbonded screeds: 50mm+. Floating screeds: 75mm+ or 65mm+ in lightly loaded/domestic locations.

ARDEX A 38

ULTRA RAPID DRYING CEMENT FOR INTERNAL AND EXTERNAL SCREEDS

8
POINTS

25kg

6
POINTS

MIX 25kg



DESCRIPTION

ARDEX A 38 has been specially formulated to produce ultra-rapid drying floor screeds for internal and external locations. With 'RAPIDRY PLUS FORMULA' Technology, an ARDEX A 38 screed can be walked on just 3 hours after application and ceramic and natural stone tiles can be installed after just 4 hours irrespective of thickness, making it ideal for fast-track tiling projects. Resilient floorcoverings such as carpet, vinyl and wood can be installed after 48 hours irrespective of thickness.


 **SUITABLE FOR EXTERNAL USE**
Yes

 **WORKING TIME**
1 hour

 **FIX TILES AFTER**
4 hours

 **USE WITH UNDERFLOOR HEATING**
Yes

 **PACK SIZE**
25kg Bag

 **COVERAGE**
3.2m² at 25mm thick or 5.4m² at 15mm thick per bag.

 **APPLICATION THICKNESS**
Bonded screeds: 15mm - 40mm
Unbonded screeds: 50mm+. Floating screeds: 75mm+ or 65mm+ in lightly loaded/domestic locations.



WALL RENDERS,
WATERPROOFING
& DPM



Waterproofing

ARDEX AM 50 OCR

STANDARD SET ONE COAT TILING RENDER



5
POINTS

DESCRIPTION

Pre-blended sand and cement render, requiring only the addition of water to produce a slump free mortar that can be applied 6-20mm thick and can be tiled in as little as 24 hours.



SUITABLE SUBSTRATES

In-situ concrete walls, brickwork, blockwork and existing render, suitable for shower



SUITABLE FOR WET AREAS

Yes



APPLICATION THICKNESS

6-20mm



POT LIFE

2 hours



FIX TILES AFTER

24 hours



PACK SIZE

25kg bag



COVERAGE

3m² per bag at 6mm thickness

ARDEX AM 100 OCR

RAPID SET ONE COAT TILE RENDER



10
POINTS

DESCRIPTION

You know that time is money, so why waste hours making walls flat for tiling with a traditional sand: cement render? ARDEX AM 100 can have damaged or uneven walls flat and ready for tiling in just two hours!



SUITABLE SUBSTRATES

In-situ concrete walls, brickwork, blockwork and existing render



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



APPLICATION THICKNESS

2-30mm



POT LIFE

30 minutes



FIX TILES AFTER

2 hours



PACK SIZE

25kg bag



COVERAGE

3.2m² per bag at 6mm thickness



WALL RENDERS, WATERPROOFING & DPM



Waterproofing

ARDEX WPC

FLEXIBLE RAPID DRYING WATERPROOF COATING FOR INTERNAL WET AREAS

DESCRIPTION

The last thing you want is your wetroom or shower areas project to fail because you neglected to adequately protect your background from water damage. ARDEX has a quick and straightforward solution with ARDEX WPC – a risk-free protective waterproof coating that prevents leaks and water damage to walls and floors. It is perfect for all types of wetroom or shower areas and can be applied easily with a roller, paintbrush or trowel. ARDEX WPC can also be used in fully submerged areas such as indoor swimming pools because it sets in just 90 minutes!

13
POINTS



SUITABLE SUBSTRATES

Concrete, sand and cement renders and screeds, gypsum plaster, plasterboard and wood-based Materials

FIX TILES AFTER 90 minutes

USE WITH UNDERFLOOR HEATING Yes

COLOURS AVAILABLE Grey - ARDEX WPC White - ARDEX WPC W

PACK SIZE 5kg bag & 5kg bottle

COVERAGE 6.6m² per 10kg unit



To waterproof, fix tiles and grout in a day, follow with ARDEX X7 R Rapid Setting Tile Adhesive and ARDEX-FLEX FL Tile Grout

ARDEX S 7 PLUS

FLEXIBLE WATERPROOF COATING FOR SWIMMING POOLS

DESCRIPTION

A waterproof/tanking coating system for use prior to fixing ceramic tiles using an appropriate ARDEX adhesive.

40
POINTS



SUITABLE SUBSTRATES

In-situ concrete walls, brickwork, blockwork and existing render

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes, including swimming pools

POT LIFE 60 minutes


FIX TILES ON THE SECOND COAT AFTER 4 hours

PACK SIZE 15kg bag

COVERAGE Approximately 6.25m² with 2 coats applied per 15kg bag



WALL RENDERS, WATERPROOFING & DPM



ARDEX DPM 1 C

ONE COAT SURFACE DAMP PROOF MEMBRANE

DESCRIPTION

ARDEX DPM 1 C is a one coat solvent free, low viscosity, two component epoxy resin. After hardening, ARDEX DPM 1 C produces a membrane which can accommodate hygrometer readings up to 98% with high inherent bond strength. ARDEX DPM 1 C has excellent resistance to water, grease, oil, aqueous salt solution and dilute mineral and organic acids.

100
POINTS


25kg

40
POINTS

10kg

25
POINTS

6kg



SUITABLE SUBSTRATES

Concrete, sand and cement renders and screeds, gypsum plaster, plasterboard and wood-based Materials

USE WITH UNDERFLOOR HEATING

Yes

WALK AFTER

6 hours

DENSITY

at 20°C: 1.54

PACK SIZE

6kg, 10kg and 25kg

COVERAGE

Refer to product datasheet



To waterproof, fix tiles and grout in a day, follow with ARDEX X 7 R Rapid Setting Tile Adhesive and ARDEX-FLEX FL Tile Grout

ARDEX WPM 200

LIQUID WATERPROOF MEMBRANE

DESCRIPTION

ARDEX WPM 200 is a solvent free, low viscosity, two component, polymer modified epoxy liquid waterproof membrane. ARDEX WPM 200 is suitable for Type A waterproof barrier protection structures as per BS 8102. After hardening ARDEX WPM 200 produces a membrane with high inherent strength and excellent bond to appropriate substrates, including very damp concrete and screeds. ARDEX WPM 200 accommodates hygrometer readings up to 98% RH and has excellent resistance to water, grease, oil, aqueous salt solution, and spillages of a range of dilute mineral and organic acids and organic liquids and solutions.

135
POINTS

20L

45
POINTS

5L



WALK AFTER

8 hours

WORKING TIME

20 minutes

DENSITY

at 20°C: 1.18



Waterproofing

ARDEX K 40 HB

3-40mm FIBRE REINFORCED LEVELLING COMPOUND

DESCRIPTION

ARDEX K 40 HB is a fibre reinforced, high build levelling and smoothing compound designed for applications from 3mm to a maximum of 40mm. It hardens rapidly and can be tiled in as little as 2 hours, regardless of thickness, which means there's minimal disruption on live sites, particularly those areas constantly in use by the customer or other trades.

3
POINTS



SUITABLE SUBSTRATES

Sand and cement screeds, gypsum screeds, concrete and flooring grade plywood



APPLICATION THICKNESS

3 -40mm



WORKING TIME

30 minutes



FIX TILES AFTER

2 hours



USE WITH UNDERFLOOR HEATING

Yes



PACK SIZE

22kg bag



COVERAGE

4m² per bag at 3mm thickness

Prime floors with **ARDEX P 51** before applying



ARDEX K 301

EXTERIOR SELF-LEVELLING CONCRETE RESURFACING COMPOUND

DESCRIPTION

ARDEX K 301 is ideal for resurfacing exterior concrete areas including driveways, garage floors, walkways, paths, patios and other concrete wearing surfaces exposed to normal foot and rubber wheeled traffic. It is also suitable for permanently wet areas and may be used around swimming pools where it can be tiled onto directly.

10
POINTS



SUITABLE SUBSTRATES

Driveways, garage floors, walkways, paths, patios and other concrete wearing surfaces



APPLICATION THICKNESS

2-20mm



WORKING TIME

30 minutes



FIX TILES AFTER

2-3 hours



USE WITH UNDERFLOOR HEATING

Yes



PACK SIZE

25kg bag



COVERAGE

Approximately 3.0m² at 5mm thickness per 25kg bag

Prime floors with **ARDEX P 51** before applying





LEVELLING



Level uneven floors and use over under tile heating cables for faster, easier, and more cost-effective tiling.

ARDITEX NA

RAPID SETTING LATEX LEVELLING COMPOUND

6
POINTS



DESCRIPTION

Why waste an entire day preparing a floor for tiling when ARDITEX NA can have it done in a matter of hours? It's a simple bag and bottle mix that can be tiled after just 3 hours. Use ARDITEX NA over most substrates without priming, including direct to bitumen, adhesive residues and ceramic tiles, and feel safe in the knowledge that your new installation will be risk-free. It can also be used to encapsulate under tile heating cables and levelling over uncoupling matting.

SUITABLE SUBSTRATES

Get even the most difficult subfloors ready to tile in a matter of hours with ARDITEX NA. Level over existing tiles, old adhesive residues, bitumen, timber* and sand and cement screeds

APPLICATION THICKNESS

Up to 30mm

WORKING TIME

20 minutes

FIX TILES AFTER

3 hours

USE WITH UNDERFLOOR HEATING

Yes

PACK SIZE

20kg bag & 4.95kg bottle

COVERAGE

5m² per unit at 3mm thickness

*Prior to overboarding with tile backing board.

ARDITEX CL

LATEX LEVELLING AND SMOOTHING COMPOUND

4
POINTS



DESCRIPTION

ARDITEX CL is a latex levelling and smoothing compound with excellent flow and application properties. ARDITEX CL receives foot traffic after as little as 2 hours and most floorcoverings can be applied 12 hours after application.

SUITABLE SUBSTRATES

Most common internal subfloors such as concrete, cement/sand and Gypsum (anhydrite) screeds.

APPLICATION THICKNESS

Up to 10mm

WORKING TIME

20 minutes

FIX TILES AFTER

12 hours

USE WITH UNDERFLOOR HEATING

Yes

PACK SIZE

20kg Powder & 4.5kg Latex

COVERAGE

Approximately 5m² at 2-3mm thick per unit.



UNCOUPLING MEMBRANES

ARDEX INDORTEC FLEXBONE 2E

FLOATING UNCOUPLING MEMBRANE FOR UNPREPARED BACKGROUNDS

DESCRIPTION

ARDEX IndorTec Flexbone 2E is a revolutionary floating uncoupling membrane from the ARDEX Group providing a full ARDEX solution for floor tiling projects. Protecting floors from lateral movement, ARDEX IndorTec Flexbone 2E is 100% uncoupled – meaning that substrates require minimal preparation.

50
POINTS




ARDEX INDORTEC FLEXBONE VA

BONDED UNCOUPLING MEMBRANE FOR PROBLEMATIC FLOORS

DESCRIPTION

Providing a full floor tiling solution from the ARDEX Group, ARDEX IndorTec Flexbone VA is a high load-bearing uncoupling mat – ideal for large format tiling in high traffic areas. The unique bone-shaped pattern with GripLock technology delivers outstanding tensile bond strength – higher than comparative cavity mat systems.

40
POINTS



Uncoupling matting adhesive

ARDEX AF 200 PLUS

READY-MIXED FLEECE-BACKED UNCOUPLING MATTING ADHESIVE

20
POINTS

14kg

8
POINTS

6kg



DESCRIPTION

Fix fleece-backed uncoupling matting faster with ARDEX AF 200 Plus – no mixing, no messing and no waiting around for the adhesive to dry before fixing your tiles. A high initial grab also stops matting systems from curling, plus it is ready-mixed, easy to apply and comes in a resealable container so it can be used again on other jobs.

Up to 45m² coverage provides a cost-effective alternative to cement-based adhesives. Suitable for all fleece-backed matting



SUITABLE SUBSTRATES

Timber, concrete and sand and cement screeds



FIX MATTING

After 5-10 minutes or within 1 hour



FIX TILES AFTER

Immediately after laying matting



USE WITH UNDEFLOOR HEATING

Yes



PACK SIZE

6kg and 14kg tubs



COVERAGE

6kg - 19m² per tub
14kg - 45m² per tub



Waterproofing properties would come from the matting manufacturer's instructions i.e. mat joints



ARDEX FIBRE-REINFORCED TILE ADHESIVES

We all know that tiles are getting bigger and heavier whilst also going onto more challenging substrates in increasingly tricky site conditions. You never know what you're going to be faced with on-site! This means that adhesives and grouts have also had to evolve to meet these new demands and provide you with the confidence to fix any tile.

The ARDEX MICROTEC range has been specifically designed to meet the challenges of today's tiling trends. Containing advanced fibre-reinforcement technology and specially developed cements and polymers.

MICROTEC® provides:

- Double the standard slump resistance of traditional tile adhesives, fixing heavy large format tiles without slipping, even without battens.
- High adhesion strength for secure fixing of modern tiles with dense, smooth undersides.
- Up to double the standard open time of traditional tile adhesives, allowing up to 60 minutes before tiles need to be fixed. Combined with the extended pot life of up to 3 hours, this allows fixers to mix, spread and fix in larger batches, and simply spend less time mixing and more time fixing!
- Up to 40% more coverage than leading competitors*, going further with every single bag and providing a cost-effective solution.



Find out about the ARDEX MICROTEC® range on p.38-39

*Comparisons based on cement-based tile adhesives' coverage and mixing data, as published on technical datasheets available on competitor websites. ARDEX MICROTEC X 77 20kg fixes up to 48 600x300mm tiles using an 8x8mm notched trowel, versus 34 600x300mm tiles using an 8x8mm notched trowel and 20kg of leading competitor tile adhesive.



READY MIXED ADHESIVE

For quick and convenient tiling

ARDEX D 20

READY MIXED WALL TILE ADHESIVE

DESCRIPTION

To make wall tiling easier, why not select a ready-mixed adhesive like ARDEX D 20? Use straight out of the bucket for fixing ceramic tiles and mosaics; it can be used in kitchens, bathrooms and domestic showers. Even better – no priming is needed, plus it is slump-free and easy to apply. Easy-peasy!

6
POINTS



SUITABLE TILES

Mosaics and ceramics up to 300mm x 300mm, porcelain up to 150mm x 150mm and porous bodied tiles when fixing tile-on-tile

SUITABLE FOR WET AREAS

Kitchens, bathrooms and domestic showers

BED THICKNESS

1-3mm

OPEN TIME

20 minutes

ADJUSTMENT TIME

40 minutes

GROUT AFTER

24 hours

PACK SIZE

10 litre tub

COVERAGE

Approximately: 1 litre per m2 using a 3mm x 3mm toothed and notched trowel.



Upgrade to **ARDEX X 77** to fix large format tiles including porcelain, and for an extended open time of up to 60 minutes!



FLEXIBLE W&F TILE ADHESIVES – STANDARD-SETTING

Confidently fix most tile types
and sizes to walls and floors

ARDEX X 7

FLEXIBLE STANDARD SET TILE ADHESIVE

4
POINTS



DESCRIPTION

Sometimes you need a little longer pot life, particularly in hotter weather or if you're tiling over larger areas. ARDEX X 7 provides excellent workability and slump resistance, as well as a pot life of up to 5 hours! It is a versatile adhesive for internal and external wall and floor applications.



SUITABLE TILES

Ceramic, porcelain, glass mosaic and non-moisture sensitive natural stone



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-6mm



POT LIFE

5 hours



OPEN TIME

30 minutes



ADJUSTMENT TIME

10 minutes



GROUT AFTER

Walls - 8 hours • Floors - 24 hours



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

Grey - ARDEX X 7 G • White - ARDEX X 7 W



PACK SIZE

20kg bag



COVERAGE

8.75m² when using a 5mm x 5mm square toothed trowel.



For up to 40% more coverage
than leading competitors,
upgrade to **ARDEX X 77**
MICROTEC Flexible Wall & Floor
Tile Adhesive

ARDEX X 11 W

ENHANCED FLEXIBLE S1 TILE ADHESIVE FOR WALLS AND FLOORS

5
POINTS



DESCRIPTION

ARDEX X 11 W is a white semi-rapid setting and hardening, cement-based, floor and wall tile adhesives. Specifically formulated to have enhanced properties of adhesion and flexibility, the excellent slump resistance properties make ARDEX X 11 W ideal for fixing large format wall tiles.



SUITABLE TILES

Ceramic, porcelain, glass mosaic and non-moisture sensitive natural stone



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-15mm



POT LIFE

2.5 hours



OPEN TIME

45 minutes



ADJUSTMENT TIME

15 minutes



GROUT AFTER

6-8 hours



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

White - ARDEX X 11 W



PACK SIZE

20kg bag



COVERAGE

A 20kg bag will be sufficient for approximately 5m² at 3mm thick.



FLEXIBLE W&F TILE ADHESIVES – STANDARD-SETTING

Fix larger tiles without
battens, get more coverage,
and easier application

ARDEX X 77

6
POINTS

MICROTEC® FLEXIBLE STANDARD SET TILE ADHESIVE

DESCRIPTION

Make fixing large tiles easier with ARDEX X 77, which is fibre-reinforced for advanced slump resistance – meaning you can fix to walls without the need for battens! 3-hour pot life and 60-minute open time allow more adhesive to be mixed, spread and fixed in a single batch, providing maximum efficiency. Cost-effective solution with up to 40% extra coverage than leading competitors*.



SUITABLE TILES

Fully vitrified or porcelain tiles, glass and porcelain mosaics, terrazzo and large format tiles



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-6mm



POT LIFE

3 hours



OPEN TIME

60 minutes



ADJUSTMENT TIME

30 minutes



GROUT AFTER

Walls - 8 hours • Floors - 24 hours



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

Grey - ARDEX X 77 • White - ARDEX X 77 W



PACK SIZE

20kg bag



COVERAGE

8m² when using an 8mm x 8mm square toothed and notched trowel.



FLEXIBLE W&F TILE ADHESIVES – RAPID-SETTING

ARDEX X 7 R

FLEXIBLE RAPID SET TILE ADHESIVE

DESCRIPTION

Do you hate having to pick either a wall or floor tile adhesive dependent on your job? ARDEX X 7 R allows water content to be adjusted to produce either a semi-pourable consistency ideal for solid bed fixing large format floor tiles or slump-free for wall tiling.

Rapid setting, versatile adhesive for internal and external floor and wall applications allow tiles to be grouted in just 2 hours, getting you onto the next job quicker! For rapid set grouting, follow with ARDEX-FLEX FL Tile Grout.

4
POINTS



SUITABLE TILES

Ceramic, porcelain, glass mosaic, terrazzo, brick slips and non-moisture sensitive natural stone



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-6mm



POT LIFE

30 minutes



OPEN TIME

Grey - 20 minutes
White - 30 minutes



ADJUSTMENT TIME

20 minutes



GROUT AFTER

2 hours



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

Grey - ARDEX X 7 R
White - ARDEX X 7 R W



PACK SIZE

20kg bag



COVERAGE

4.7m² per bag at 3mm thickness



FLEXIBLE W&F TILE ADHESIVES – RAPID-SETTING

ARDEX X 77 S

MICROTEC® FLEXIBLE RAPID SET TILE ADHESIVE

DESCRIPTION

ARDEX X 77 S is a grey MICROTEC fibre reinforced, ultra rapid setting and hardening, cement-based, floor and wall tile adhesives. Specifically formulated to have enhanced properties of adhesion and flexibility, the advanced slump resistance properties make ARDEX X 77 S ideal for fixing large format wall tiles. Coverage: 9.5m² when using a 5mm x 5mm square toothed and notched trowel.

8
POINTS



SUITABLE TILES

Moisture and non-moisture sensitive natural stone, agglomerated stone, porcelain, mosaics, fully vitrified and ceramic tiles

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

BED THICKNESS

1-6mm

POT LIFE

30 minutes

OPEN TIME

20 minutes

ADJUSTMENT TIME

15 minutes

GROUT AFTER

90 minutes

USE WITH UNDERFLOOR HEATING

Yes

COLOUR AVAILABLE

Grey - ARDEX X 77 S

PACK SIZE

20kg bag

COVERAGE

20kg bag of ARDEX X 77 S will cover approximately 9.5m² when using a 5mm x 5mm square toothed and notched trowel.



Also available as semi-pourable
for floors **ARDEX S 28**

ARDEX S 27

MICROTEC® FLEXIBLE RAPID SET TILE & STONE ADHESIVE

DESCRIPTION

We know that speed is of the essence, especially when fixing natural stone. ARDEX S 27 rapid-drying, fibre-reinforced tile adhesive combines the use of MICROTEC with 'RAPIDRY FORMULA' Technology for speed and assurance when you're fixing natural stone. Ideal for fixing all stone tiles, ARDEX S 27 virtually eliminates the risks of staining and warping and allows grouting to commence after just 2 hours.

10
POINTS



SUITABLE TILES

Moisture and non-moisture sensitive natural stone, agglomerated stone, porcelain, mosaics, fully vitrified and ceramic tiles

SUITABLE FOR EXTERNAL USE OR WET AREAS

No

BED THICKNESS

1-15mm

POT LIFE

60 minutes

OPEN TIME

30 minutes

ADJUSTMENT TIME

15 minutes

GROUT AFTER

2 hours

USE WITH UNDERFLOOR HEATING

Yes

COLOUR AVAILABLE

White - ARDEX S 27 W

PACK SIZE

20kg bag

COVERAGE

6.4m² per bag at 3mm thickness



Also available as semi-pourable
for floors **ARDEX S 28**



POURABLE FLOOR ADHESIVES

ARDEX X 78

MICROTEC® FLEXIBLE STANDARD SET SEMI-POURABLE FLOOR TILE ADHESIVE

DESCRIPTION

ARDEX X 78 S grey is a MICROTEC fibre reinforced, ultra rapid setting cement-based floor tile adhesive which can be walked on and grouted after only 90 minutes. Specifically formulated to have enhanced properties of adhesion and flexibility, its unique semi-pourable consistency makes it for fixing large format floor tiles.

SUITABLE TILES

Ideal for all tile types including porcelain, fully vitrified, mosaics and terrazzo

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

BED THICKNESS

1-6mm

POT LIFE

30 minutes

OPEN TIME

60 minutes

ADJUSTMENT TIME

30 minutes



Grout in just 90 minutes with **ARDEX X 78 S**

8
POINTS



ARDEX X 325 PTB

POURABLE THICK BED TILE ADHESIVE

DESCRIPTION

ARDEX X 325 PTB is our pourable thick bed tile adhesive that's the ideal all-in-one product for levelling uneven floors and fixing large format floor tiles. Apply 3-25mm to level uneven floors and fix tiles in a single application.

SUITABLE TILES

All tile types, including vitrified, porcelain, and agglomerate and natural stone

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

BED THICKNESS

3-25mm

POT LIFE

30 minutes

OPEN TIME

20 minutes

ADJUSTMENT TIME

10 minutes

GROUT AFTER

3 hours

USE WITH UNDERFLOOR HEATING

Yes

COLOURS AVAILABLE

Grey – ARDEX X 325 PTB
White – ARDEX X 325 PTB W


PACK SIZE

20kg bag

COVERAGE

4.8m² per bag at 3mm thickness

4
POINTS





POURABLE FLOOR ADHESIVES

Ideal for fixing on timber floors

ARDEX X 7001

MICROTEC® FLEXIBLE RAPID SET POURABLE FLOOR TILE & STONE ADHESIVE

8
POINTS



DESCRIPTION

Need to tile on timber floors? ARDEX X 7001 makes floor tiling easy for you with its fibre-reinforced, pourable formulation. This helps you achieve solid-bed fixing on most subfloors and is particularly effective on wood-based sheets and boards. 'RAPIDRY FORMULA' Technology locks in the mix water, helping to reduce warping and movement in timber floors, as well as discolouration and staining in moisture sensitive natural stone.

SUITABLE TILES

All tile types, including vitrified, porcelain, and agglomerate and natural stone

SUITABLE FOR EXTERNAL USE OR WET AREAS

No

BED THICKNESS

1-6mm

POT LIFE

60 minutes



Prime timber with ARDEX P 51 before applying ARDEX X 7001

OPEN TIME

30 minutes

ADJUSTMENT TIME

15 minutes

GROUT AFTER

90 minutes

USE WITH UNDERFLOOR HEATING

Yes

COLOURS AVAILABLE

Grey - ARDEX X 7001 White - ARDEX X 7001 W

PACK SIZE

20kg bag

COVERAGE

4.8m² per bag at 3mm thickness

ARDEX S 28 W

MICROTEC® FLEXIBLE RAPID SET SEMI-POURABLE FLOOR TILE & STONE ADHESIVE

11
POINTS



DESCRIPTION

ARDEX S 28 combines the use of MICROTEC with RAPIDRY FORMULA Technology to virtually eliminate the risks of staining and warping and grouting can commence after just 2 hours, regardless of bed thickness. The semi-pourable consistency makes it ideal for solid bed fixing large format floor tiles and slabs.

SUITABLE TILES

Moisture and non-moisture sensitive natural stone, agglomerated stone, porcelain, mosaics, fully vitrified and ceramic tiles

SUITABLE FOR EXTERNAL USE OR WET AREAS

No

BED THICKNESS

1-15mm

POT LIFE

60 minutes

OPEN TIME

30 minutes

ADJUSTMENT TIME

15 minutes

GROUT AFTER

2 hours

USE WITH UNDERFLOOR HEATING

Yes

COLOURS AVAILABLE

White - ARDEX S 28 W

PACK SIZE

20kg bag

COVERAGE

6m² per bag at 3mm thickness



POURABLE FLOOR ADHESIVES

ARDEX X 78 S

MICROTEC® FLEXIBLE RAPID SET SEMI-POURABLE FLOOR TILE ADHESIVE

DESCRIPTION

ARDEX X 78 S has been specifically engineered to fit today's tiles with ease. It also provides additional performance benefits that support modern fixing practices, particularly its semi-pourable mix consistency and rapid setting characteristics.

9
POINTS



SUITABLE TILES

All tile types, including vitrified porcelain and agglomerate and natural stone



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-6mm



POT LIFE

30 minutes



OPEN TIME

30 minutes



ADJUSTMENT TIME

15 minutes



GROUT AFTER

90 minutes



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

Grey - ARDEX X 78 S



PACK SIZE

20kg bag



COVERAGE

9.4m² when using a 5mm x 5mm square toothed and notched trowel.

ARDEX X 32

FLEXIBLE RAPID SET THICK BED TILE & STONE ADHESIVE FOR EXTERNAL AREAS

DESCRIPTION

ARDEX X 32 Natural Stone Adhesive is classified as C2 FTE S1 "Improved deformable fast setting cementitious adhesive with reduced slip and extended open time" in accordance with BS EN 12004. ARDEX X 32 Natural Stone Adhesive is a special rapid hardening and drying, white cement-based adhesive for fixing natural stone floor and wall tiles including moisture sensitive natural stone tiles and uncalibrated natural stone floor tiles. It may also be used for concrete slabs and ceramic tiles including porcelain tiles in internal and external situations.

10
POINTS



SUITABLE TILES

All tile types, including vitrified porcelain and agglomerate and natural stone



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



BED THICKNESS

1-6mm



WORKING TIME

60 minutes



OPEN TIME

20 minutes



ADJUSTMENT TIME

20-30 minutes



GROUT AFTER

3 hours



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

White - ARDEX X 32



PACK SIZE

20kg bag



COVERAGE

5.5m² per bag at 3mm thickness



ARDEX E 90

ADMIX IMPROVER FOR CEMENT-BASED TILE ADHESIVES

12
POINTS



DESCRIPTION

ARDEX E 90 is a special synthetic dispersion for use with ARDEX X 7 G, ARDEX X 7 W and ARDEX S 21 cement based adhesives. ARDEX E 90 is diluted with an equal volume of water prior to mixing with the ARDEX adhesive powder. The addition of ARDEX E 90 produces a mortar that, once set and hardened, has high adhesive strength, elastic and water repellent properties.

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

USE WITH UNDERFLOOR HEATING

Yes

PACK SIZE

3.6kg

COVERAGE

2kg of ARDEX E 90 is sufficient for approximately 22kg of ARDEX S 21

Easier tiling on
problematic substrates

ARDEX X 60 PU FLEX

POLYURETHANE REACTION RESIN TILE ADHESIVE

25
POINTS



DESCRIPTION

Fixing to fibreglass (GRP), steel and PVC coverings can be difficult without specialist products like ARDEX X 60 PU FLEX. A two-part polyurethane adhesive, it can be used directly on to these surfaces without priming. It's also suitable for moisture-sensitive materials, making it ideal for use with natural stone tiles and substrates such as plywood, plasterboard and particle board. It is easy to apply and requires no special tools, making your job easier!

SUITABLE TILES

All tile types, including vitrified porcelain and agglomerate and natural stone

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

BED THICKNESS

1-5mm

POT LIFE

45 minutes

OPEN TIME

60 minutes

GROUT AFTER

3 hours

USE WITH UNDERFLOOR HEATING

Yes

COLOURS AVAILABLE

White

PACK SIZE

3kg metal container

COVERAGE

Please refer to TDS.



CEMENT BASED GROUTS

Blended to a uniform colour,
ensuring a consistent,
streak-free finish

ARDEX-FLEX FS

FLEXIBLE STANDARD SET TILE GROUT FOR NARROW JOINTS

DESCRIPTION

When finishing your tiling project, you want a grout that provides a clean, fresh look that is resistant to wear and tear. ARDEX-FLEX FS does just that, as a water-repellant and dirt resistant, flexible grout. Use for wall and floor joints up to 4mm; it is blended to a uniform colour, giving you a consistent, streak-free finish. Suitable for commercial and domestic locations, including swimming pools, showers and kitchens. Easy to apply and clean off the surface of the tile.

 **SUITABLE TILES**
Porcelain, ceramic, quarry tiles,
extruded tiles and glass mosaics

 **SUITABLE FOR EXTERNAL
USE OR WET AREAS**
Yes

 **JOINT WIDTH**
Up to 4mm

 **WORKING TIME**
2½ hours


 **WALKABLE AFTER**
5 hours

 **USE WITH UNDERFLOOR HEATING**
Yes

 **PACK SIZE**
2.5kg, 5kg and 10kg bags

 **COLOURS AVAILABLE**
Available in 2.5kg, 5kg, 10kg: Brilliant White, Dove Grey, Silver Shimmer, Fresh Snowdrop, Ocean Grey, Cast Iron, Antique Ivory, Black, Slate Grey, Spring Jasmine, Stormy Mist, Gentle Dawn, Winter White, Stone Beach, Natural Almond, Blossom White, Classic Vanilla, Floating Driftwood, Gentle Blush, Grey Dusk, Coffee Bean.
Available in 2.5kg, 10kg: Organic Earth, Wild Mushroom, Weathered Ash, Barley Sugar, Pebble Drift, Woodland Taupe, Oyster Pink, Ground Cocoa, Burnt Orange, Spring Green, Summer Yellow, Autumn Red, Pecan Syrup, Fresh Magnolia

6
POINTS
10kg
3
POINTS
5kg
2
POINTS
2.5kg



Rapid setting ARDEX-FLEX FL

FLEXIBLE RAPID SET TILE GROUT FOR WIDE JOINTS

DESCRIPTION

If you're grouting wider joints, look for ARDEX-FLEX FL – a rapid-setting tile grout for wall and floor joints from 3-15mm wide. Tiles can be trafficked after just 90 minutes, meaning you finish that job sooner, blended to a uniform colour, ensuring a consistent, streak-free finish throughout your project. Suitable for commercial and domestic locations, including swimming pools, showers and kitchens, it is easy to apply and clean off the tile's surface.

 **SUITABLE TILES**
Porcelain, ceramic, quarry tiles,
extruded tiles and glass blockwork

 **SUITABLE FOR EXTERNAL
USE OR WET AREAS** Yes

 **JOINT WIDTH**
3-15mm

 **WORKING TIME**
30 minutes

 **WALKABLE AFTER**
90 minutes

 **USE WITH UNDERFLOOR HEATING**
Yes

6
POINTS
10kg
3
POINTS
5kg
2
POINTS
2.5kg



 **COLOURS AVAILABLE**
35 colours
 **PACK SIZE** 2.5kg, 5kg and 10kg bags

 **COLOURS AVAILABLE**
Available in 2.5kg, 5kg and 10kg: Dove Grey, Stormy Mist, Black, Ocean Grey, Cast Iron.

Available in 2.5kg and 10kg: Silver Shimmer, Spring Jasmine, Natural Almond, Slate Grey, Fresh Snowdrop, Floating Driftwood, Gentle Dawn, Brilliant White, Antique Ivory, Classic Vanilla, Gentle Blush, Stone Beach, Organic Earth, Winter White, Grey Dusk, Barley Sugar, Blossom White, Woodland Taupe, Wild Mushroom, Coffee Bean, Weathered Ash, Pebble Drift, Ground Cocoa, Burnt Orange, Oyster Pink, Fresh Magnolia, Autumn Red, Spring Green, Summer Yellow, Pecan Syrup.



CEMENT BASED GROUTS


ARDEX MG

FLEXIBLE RAPID SET TILE & STONE GROUT

DESCRIPTION

When grouting moisture sensitive stone and marble, one of the most significant risks is water staining. Get it wrong, and you could be looking at costly remedial work! To eliminate this risk, you could try ARDEX MG – a quick-setting grout that contains ARDEX RAPIDDRY FORMULA Technology which binds the mix water within the grout.

8
POINTS



SUITABLE TILES

Moisture and non-moisture sensitive natural stone, agglomerated stone, porcelain, mosaics, fully vitrified and ceramic tiles

SUITABLE FOR EXTERNAL USE OR WET AREAS

No

JOINT WIDTH

Up to 8mm

WORKING TIME

30 minutes

WALKABLE AFTER

90 minutes


USE WITH UNDERFLOOR HEATING

Yes


PACK SIZE

11kg bag

COLOURS AVAILABLE



White




Light Grey



Dark Grey



Sandstone



Limestone

*Due to the printing process, all colours are for guidance only.



EPOXY GROUTS

ARDEX WA

EPOXY TILE GROUT & ADHESIVE

DESCRIPTION

ARDEX WA is a solvent free, epoxide resin-based thin bed adhesive and grouting compound, for use where chemical resistance is required or where cement-based grouts are inappropriate. ARDEX WA is suitable for fixing and grouting all types of ceramic tiles, glass and ceramic mosaics in internal and external situations. When fully cured, the ARDEX WA mortar provides a decorative, waterproof, weather and frost resistant joint from 2-12mm wide that is chemically resistant.

11
POINTS



SUITABLE SUBSTRATES

Glazed and unglazed tiles including natural stone, enamel, glass, acrylic, anodised aluminium, plastics, laminated kitchen work boards, thicker varnishes and wood

SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes

WORKING TIME

85 minutes

USE WITH UNDERFLOOR HEATING

Yes

JOINT WIDTH

2-12mm

COLOURS AVAILABLE

White & Grey

PACK SIZE

4kg (White & Grey) & 2kg (White only).

COVERAGE

A 4kg unit of ARDEX WA is sufficient for approximately 1.4m² of tiles or 2.2m² of medium or small mosaics.



EPOXY GROUTS



ARDEX EG 18 PLUS

EASY APPLY & CLEAN EPOXY TILE GROUT & ADHESIVE

12
POINTS



DESCRIPTION

Combining the chemical resistance of epoxy grouts and the ease of application of cement-based grouts, ARDEX EG 18 Plus is ideal where high standards of hygiene and waterproofing are required. It is easier to clean after application and ensures a reduced maintenance schedule; it requires no specialist tools and can be cleaned off the tile surface up to 60 minutes after application. This gives you more time to grout and clean off, making your installation easier.



SUITABLE TILES

Most tiles, including ceramics, porcelain, glass mosaics, quarry tiles etc



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



JOINT WIDTH

Up to 2mm to 12mm



POT LIFE

60 minutes



WALKABLE AFTER

12 hours



USE WITH UNDERFLOOR HEATING

Yes




PACK SIZE

4kg tub

COLOURS AVAILABLE


*Due to the printing process, all colours are for guidance only.



White



Grey



Silver Grey



Bahama Beige



Anthracite



SILICONES

Easy application



Mix the resin and hardener together



Mix in the filler



Apply ARDEX EG 18 PLUS with a
hard rubber grout float



When ready to wash off, spray a fine mist of
water over the face of the tile



Clean down the tile surface to
remove grout residues



Finished application



SILICONES



ARDEX ST

NEUTRAL CURE ELASTIC SILICONE SEALANT

2
POINTS



DESCRIPTION

Get the perfect finish to your tiling project with ARDEX ST neutral cure silicone sealant for movement joints, corner and connecting joints in bathrooms, showers and living areas, plus doors and windows abutting tiles. Weather, water, UV radiation and chemical resistant, it also contains fungicide to prevent the growth of fungi and moulds, providing your clients peace of mind for long-lasting protection. Suitable for use with most surface finishes, including moisture sensitive natural stone.



SUITABLE SUBSTRATES

Glazed and unglazed tiles including natural stone, enamel, glass, acrylic, anodised aluminium, plastics, laminated kitchen work boards, thicker varnishes and wood



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



SKIN FORMING TIME

5 minutes



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

Transparent & 13 colours designed to match the most popular ardex-flex tile grout colours



PACK SIZE

310ml cartridge



COVERAGE

8.6m per cartridge with 6mm x 6mm bead

Turn to p.38 & 39 for our Tile Grout & Silicone Colour Guide and order colour samples online at www.ardex.co.uk



ARDEX CA 20 P

MULTI-PURPOSE CONSTRUCTION ADHESIVE & SEALANT

2
POINTS



DESCRIPTION

ARDEX CA20P is an extremely flexible, single component adhesive and sealant, with excellent bond strength. It is suitable for a wide range of applications as both an adhesive and sealant for floors, walls and general building maintenance in internal or external situations.



SUITABLE SUBSTRATES

Glazed and unglazed tiles including natural stone, enamel, glass, acrylic, anodised aluminium, plastics, laminated kitchen work boards, thicker varnishes and wood



SUITABLE FOR EXTERNAL USE OR WET AREAS

Yes



SKIN FORMING TIME

7-10 minutes



USE WITH UNDERFLOOR HEATING

Yes



COLOURS AVAILABLE

White & Grey



PACK SIZE

310 cartridge



COVERAGE

9.75m per cartridge with 6mm x 6mm bead



TILE GROUTS & SILICONES COLOUR GUIDE

ORDER COLOUR
SAMPLES ONLINE
ardex.co.uk

01

Available in ARDEX ST

Brilliant White

02

Blossom White

03

Available in ARDEX ST

Antique Ivory

04

Available in ARDEX ST

Spring Jasmine

05

Gentle Dawn

06

Available in ARDEX ST

Natural Almond

07

Classic Vanilla

08

Available in ARDEX ST

Floating Driftwood

09

Fresh Snowdrop

10

Gentle Blush

11

Stone Beach

12

Barley Sugar

13

Fresh Magnolia

14

Wild Mushroom

15

Oyster Pink

16

Organic Earth

17

Available in ARDEX ST

Dove Grey

18

Available in ARDEX ST

Silver Shimmer

19

Available in ARDEX ST

Ocean Grey

20

Available in ARDEX ST

Slate Grey

21

Pebble Drift

22

Grey Dusk

23

Available in ARDEX ST

Stormy Mist

24

Available in ARDEX ST

Cast Iron

25

Available in ARDEX ST

Black

26

Available in ARDEX ST

Coffee Bean

27

Ground Cocoa

28

Burnt Orange

29

Winter White

30

Spring Green

31

Summer Yellow

32

Autumn Red

33

Weathered Ash

34

Woodland Taupe

35

Pecan Syrup

Due to the printing process, all colours are approximate.

TECHNICAL SUPPORT

WHEN AND WHERE YOU NEED IT MOST



TECHNICAL
ADVICE



SITE
SUPPORT



MOISTURE
TESTS



SPECIFICATION
WRITING



TRAINING

OUR EXPERIENCED TEAM ARE AVAILABLE NATIONWIDE TO OFFER ADVICE,
SUPPORT AND TRAINING, NOT JUST OVER THE PHONE,
BUT IN PERSON AND ON-SITE.



ARDEX UK Limited
01440 714939

@ARDEXUKFlooring
info@ardex.co.uk

f ARDEX UK
www.ardex.co.uk

in ARDEX UK

ARDEXacademy

TRAINING EXCELLENCE

We offer a range of training
courses that can be tailored
to your specific needs.

Carried out by our team of technical experts
who have extensive knowledge and practical
experience of the construction industry, our
courses cover the latest technological
advances and industry regulations.

BOOK YOUR
TRAINING
PLACE NOW




CONTACT US

Call our Training Administrator on
01440 714949 or email info@ardex.co.uk





NOTES



Scan QR Code to visit our website.



Ardex UK Limited

Homefield Road Haverhill Suffolk CB9 8QP United Kingdom

Tel: 01440 714939 Email: info@ardex.co.uk



ardex.co.uk