The Ultimate Uncoupling Matting Installation System



Install matting systems quicker, easier and more cost-effectively





Install floorcoverings after 4 hours, and ceramic tiles in as little as 3 hours Can be used with confidence over old adhes residues including bitumen

Excellent adhesion without priming to almo

Unaffected by moisture, can be used under a ARDEX Damp Proof Membrane and direct to dama constant.

Constructive contract of the construction of the construction



Suitable for all fleece-backed matting and ideal for Schlüter[®]- DITRA

> by Schlüter Systems

ARDEX AF 200 PLUS UNCOUPLING MATTING ADHESIVE

Install Matting Quicker, Easier & More Cost-Effectively

- Minimises the time required to install fleece-back uncoupling matting
- Fix matting to timber, concrete and cement/sand screed subfloors without priming
- Matting can be fixed after 5-10 minutes or, due to its long tack time, up to an hour after application
- High grab formulation prevents curling of the mat for easy installation
- Once matting is installed, ARDITEX NA Ultra Rapid Setting Latex Levelling Compound can be applied immediately

1.25-

- Cost-effective with up to 45m² coverage from a single tub
- Ready mixed and resealable

ARDITEX NA ULTRA RAPID SETTING LATEX LEVELLING COMPOUND

- Creates a flat and level surface ideal for tiling
- Quickly and easily fills matting cavities and levels
 substrate deviations
- Removes the need to pack-out with extra tile adhesive
- Ready to receive tiles after just 3 hours
- High coverage every unit covers up to 10m² of matting



3HIB

20^{kg}

DITEX NA



Ready for use, ARDEX AF 200 PLUS doesn't require mixing. Simply pour directly onto the floor without priming.



Matting can be fixed after 5-10 minutes or, due to its long tack time, up to an hour after application. High grab formulation prevents curling of the mat for easy installation.



ARDITEX NA can be tiled onto after just 3 hours with an ARDEX Cement-Based Tile Adhesive.

For technical support and advice, and for orders and sales enquiries, please contact ARDEX on 01440 714939.



For maximum coverage, spread ARDEX AF 200 PLUS with a B1 or $2mm \times 6mm$ v-notch serrated trowel. When finished, reseal the tub ready for the next job.



Matting can be levelled immediately with ARDITEX NA, to quickly and easily create a flat, level surface.



Finish with an ARDEX-FLEX Tile Grout & ARDEX ST Silicone Sealant, available in a wide range of colours.

@ARDEXUKTiling





ARDEX UK

The Ultimate Uncoupling Matting Installation System

Install matting systems quicker, easier and more cost-effectively













ARDEX UK Limited Tel: 01440 714939



Email: info@ardex.co.uk

f ARDEX UK

ARDEX online: www.ardex.co.uk