



**DECLARATION OF PERFORMANCE**  
**in accordance with Annex III of Regulation (EU) No. 305/2011**  
**(Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No 574/2014**

**No.000076**

1. Unique identification code of the product type:

**ARDEX WPC White**  
**EN 14891:CM02P**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Cementitious liquid-applied water impermeable product with improved crack bridging ability at very low temperature (-20 °C) and resistant to contact with chlorinated water (bonded with a C2 adhesive in accordance with EN 12004)**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer:

**ARDEX UK Ltd**  
**Homefield Road**  
**Haverhill**  
**Suffolk CB9 8QP**  
**United Kingdom**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the Regulation (EU) No 305/2011:

**not applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body **LGAI TECHNOLOGICAL CENTER, S. A./Applus** with the identification number **0370** performed the test according to EN 14891:2012.

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:

**not applicable**

7. Declared Performance

Essential characteristics	Performance	Harmonised technical specification
Bond strength as: - initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	EN14891:2012
Durability for: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion after freeze thaw cycles	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Tensile adhesion strength after contact with lime water	$\geq 0.5\text{N/mm}^2$	
Water Impermeability	No penetration	
Crack bridging ability in standard conditions	$\geq 0.75\text{ mm}$	
Tensile adhesion strength after contact with chlorinated water	$\geq 0.5\text{N/mm}^2$	
Crack bridging ability at low temperature (-5°C)	$\geq 0.75\text{mm}$	
Crack bridging ability at very low temperature (-20°C)	$\geq 0.75\text{mm}$	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Ian Smith, Laboratory Manager  
Haverhill

13/04/2017