

RENOVATION COMPOUND & LIGHTWEIGHT HIGH BUILD REPAIR MORTAR

ARDEX A 950



ARDEX A 950 is a multi-purpose lightweight high build repair mortar that can be used to repair walls and floors. ARDEX A 950 can be applied from 2mm to 100mm, and will harden in as little as 1 hour, regardless of thickness.

- Polymer Modified Cementitious Lightweight Repair Mortar for Internal Use
- Slump free, apply from 2mm to 100mm
- Can receive finishes after 24 hours regardless of thickness
- Ideal for general building work, filling large cavities and deep holes around door frames
- No priming required
- Non-combustible – Reaction to fire Class A1 (EN 13501-1)
- Low-tension and shrinkage compensated, even in thick layers

RAPID DRY
FORMULA



Installation Schedule

APPLICATION DEPTH:
2-100mm




WORKING TIME:
30-40 minutes



DRYING TIME:
From 90 minutes



COVERAGE:
8m² at 3mm thick



Pack Size



Suitable for:

- ✓ Internal floors, walls and ceilings
- ✓ Large cavities and deep holes
- ✓ Dot and dab fixing of plasterboards
- ✓ Boxing in pipework
- ✓ Making columns and pedestals
- ✓ Modelling architectural features
- ✓ Electrical chases