

INTRODUCING

OUR PRESSURE SENSITIVE FLOORING ADHESIVES



OUR PRESSURE SENSITIVE FLOORING ADHESIVES

ARDEX PRESSURE SENSITIVE CONTRACT ADHESIVE ARDEX AF 148

- 3 hour working time, ideal for large projects
- Exceptional final bond strength
- Excellent coverage, up to 52m² per 10kg tub

INSTALLATION SCHEDULE



I FGFND. AIRING TIME:

> The time the adhesive must be left open before applying the floorcovering.

The time in which the adhesive can receive the floorcovering, after the initial airing time. OPEN TIME:

The combination of airing and working

Times dependent on the absorbency of the subfloor and site conditions.

ARDEX PRESSURE SENSITIVE VINYL ADHESIVE **ARDEX AF 145**

- Can be used as a wet set or pressure sensitive adhesive
- Ready to receive floorcoverings in as little as 20 minutes
- Can receive vinyl sheet up to 80 minutes after airing

INSTALLATION SCHEDULES



Times dependent on the absorbency of the subfloor and site conditions.

A1 Up to 48m²





ARDEX Flooring Adhesives meet the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible, or very low emission limits.

ARDEX AF 148 and AF 145 are part of the ARDEX Flooring Adhesive range, for further information or to view our Technical Datasheets please visit www.ardex.co.uk



THINK RED. TRUST ARDEX.









