



SAFETY DATA SHEET Ardex EG 18 Hardener

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Ardex EG 18 Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As part of an epoxy resin based adhesive or grout.

1.3. Details of the supplier of the safety data sheet

Supplier Ardex UK Limited
Homefield Road
Haverhill
Suffolk
CB9 8QP
01440 714939

Contact person safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency telephone UK and ROI:- 01865 407 333 (available 24/7/365)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H318 Causes serious eye damage.

Ardex EG 18 Hardener

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine, 1,3- Cyclohexanedimethanamine, 3-AMINOPROPYLTRIETHOXYSILANE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	60-100%
CAS number: 68082-29-1	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
1,3- Cyclohexanedimethanamine	10-30%
CAS number: 2579-20-6 EC number: 219-941-5	
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Aquatic Chronic 3 - H412	
3-AMINOPROPYLTRIETHOXYSILANE	1-5%
CAS number: 919-30-2 EC number: 213-048-4	
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove affected person from source of contamination. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
-------------------	--

Ardex EG 18 Hardener

Ingestion	DO NOT induce vomiting. Get medical attention immediately. Rinse mouth thoroughly with water. Give plenty of water to drink.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Continue to rinse for at least 15 minutes. Get medical attention. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention immediately.
Inhalation	Gas or vapour may irritate the respiratory system.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Causes severe burns.
Eye contact	Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	In case of fire, toxic and corrosive gases may be formed. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
-------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid or minimise the creation of any environmental contamination.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Do not touch or walk into spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ardex EG 18 Hardener

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Corrosive storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

The product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Personal protection

The following recommendations are made based on information available for the major chemical component.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Use protective gloves. Nitrile rubber. Protective gloves should have a minimum thickness of 0.5 mm.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station and safety shower. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Combination filter, type A2/P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Amber.
Odour	Amine.
Flash point	> 100°C (Non Flammable)
Solubility(ies)	Not miscible or difficult to mix.
Viscosity	202 mPa s @ 25°C

Ardex EG 18 Hardener

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No further information available.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Alkali metals. Zinc, Nitrates, Peroxide.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 3,213.0

Inhalation Vapour may irritate respiratory system/lungs.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin contact May cause skin irritation/eczema.

Eye contact Causes burns.

SECTION 12: Ecological information

Ecotoxicity No data on possible environmental effects have been found.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: 7.07 mg/l, Fish

Acute toxicity - aquatic plants LC₅₀, 72 hour: 1.25 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability No further relevant information available.

12.3. Bioaccumulative potential

Bioaccumulative potential No further relevant information available.

12.4. Mobility in soil

Ardex EG 18 Hardener

Mobility No further information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 00 00 wastes from the manufacture, formulation, supply and use (MFSU) of coatings (peaints, varnishes. and vitreous enamels), adhesives, sealants and printing inks. 08 02 00 Wastes from MFSU of other coatings (including ceramic materials). 08 02 99 Wastes not otherwise specified.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 2735

UN No. (IMDG) 2735

UN No. (ICAO) 2735

UN No. (ADN) 2735

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- Cyclohexanedimethanamine, Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)

Proper shipping name (IMDG) AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- Cyclohexanedimethanamine, Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)

Proper shipping name (ICAO) AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- Cyclohexanedimethanamine, Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)

Proper shipping name (ADN) AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- Cyclohexanedimethanamine, Fatty acids, C18 unsat, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C7

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Ardex EG 18 Hardener

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

IMDG Code segregation group	18. Alkalis
EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.
----------	--

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments	1
Issued by	Head of R+D
Revision date	20/12/2021
SDS number	20660

Ardex EG 18 Hardener

Hazard statements in full

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.