

**DECLARATION OF PERFORMANCE**  
**In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No. 574/2014**  
**for the product Ardex EG18 Plus colours other than white**  
**No. 000080-CPR/2013**

1. Unique identification code of the product-type:  

**EN 12004:2007 + A1:2012**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  

**Improved reaction resin adhesive.**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):  

**Ardex UK Limited,  
Homefield Road,  
Haverhill,  
Suffolk,  
CB9 8QP**
4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  

**Not applicable**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  

**System 3**
- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  

**EN 12004:2007+A1:2012**

**The Notified Body 0370 carried out the determination of the product type on the basis of type testing on samples provided on behalf of Building Adhesives Limited under System 3 and issued test report 21/32301127. Reaction to fire performance has been declared in accordance with the Commission Decision of 9<sup>th</sup> February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.**


- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  

**Not applicable**
7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	≥ 2.0Nmm <sup>-2</sup>	
Durability for; - shear adhesion strength after water immersion - shear adhesion strength after thermal shock	≥ 2.0Nmm <sup>-2</sup> ≥ 2.0Nmm <sup>-2</sup>	
Release of dangerous substances	See MSDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 amended by Commission Delegated Regulation (EU) No. 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D



Stoke on Trent 03/10/22