

# Sustainability data sheet

## ARDEX A 950

### Flex Putty, grey

For smoothing and levelling of wall and ceiling areas. For tiles and other coverings  
Levelling of floor areas, filling of bigger grooves.

#### Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

**EMICODE® EC 1<sup>PLUS</sup>**,  
very low emission



According French VOC Classification

**A+**



solvent-free

#### EPD (Environmental Product Declaration)

ARDEX A 950 corresponds to FEICA EPD:

**EPD-DBC-20220217-IBF1-EN**

## Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE ZP1** - cementitious product, low-chromate

## Sustainable Building

#### According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

##### Version 2018

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX A 950 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX A 950 has the GISCODE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX A 950 fulfills the requirements for highest Quality Level 4.**

##### Version 2015

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX A 950 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX A 950 is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX A 950 fulfills the requirements for highest Quality Level 4.**

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



# ARDEX A 950

Flex Putty, grey

## Sustainable Building

According LEED (Leadership in Energy and Environmental Design)

### Version 4 (2014)

#### EQ: Low Emitting Materials

ARDEX A 950 meets the requirements according EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV which are accepted by LEED.

**ARDEX A 950 meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.**

#### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX A 950 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX A 950 meets the requirements and contributes to achieving one LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

### Version 2009

#### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

Cementitious fillers are not described by LEED.

#### MR Credit 5.1 und 5.2: Regional Materials

##### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 09/03/2023

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
www.ardex.de

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
kundendienst@ardex.de  
www.ardex.de

