

Sustainability data sheet

ARDEX-FLEX FS Flexible Standard Set Tile Grout for Narrow Joints

ARDEX-FLEX FS is formulated to blend to a uniform colour, ensuring a consistent, streak-free finish, and it is suitable for commercial and domestic locations including swimming pools, showers and kitchens.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

EMICODE® EC 1^{PLUS},
very low emission



solvent-free

EPD (Environmental Product Declaration)

ARDEX-FLEX FS corresponds to FEICA EPD:

EPD-DBC-20220218-IBF1-EN

Technical Assessment

According **GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe)**:

GISCODE ZP1 - cementitious product, low-chromate

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



Sustainable Building

ARDEX-FLEX FS

Flexible Standard Set Tile Grout for Narrow Joints

Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

Version 2018

DGNB criteria ENV 1.2: Local environmental impact

ARDEX-FLEX FS is not relevant to the evaluation according DGNB.

ARDEX-FLEX FS has the GISOCDE ZP1 and is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX-FLEX FS fulfills the requirements for highest Quality Level 4.

Version 2015

DGNB criteria ENV 1.2: Local environmental impact

ARDEX-FLEX FS can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX-FLEX FS is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX-FLEX FS fulfills the requirements for Quality Level 4.

Accordinging LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX-FLEX FS meets the requirements according EMICODE® EC 1^{PLUS}, very low emission, based on GEV and A+ based on French VOC Classification which are accepted by LEED.

ARDEX-FLEX FS meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX-FLEX FS corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX-FLEX FS fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX-FLEX FS according SCAQMD Rule 1168 is < 65 g/L.

ARDEX-FLEX FS meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de

ARDEX-FLEX FS

Flexible Standard Set Tile Grout for Narrow Joints

According BREEAM (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM criteria Hea 02 Indoor air quality

ARDEX-FLEX FS can be classified as Flooring materials (including floor levelling compounds and resin flooring). ARDEX-FLEX FS meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX-FLEX FS is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX-FLEX FS meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 10/03/2023

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de

