

# Sustainability data sheet

## ARDEX R 5 E Fast Cure Epoxy Primer

Fast curing

Overcoat after only 4 hours

Can be sand blinded for thicker flooring systems

### Emissions

According GEV (Gemeinschaft  
Emissionskontrollierte  
Verlegewerkstoffe, Klebstoffe und  
Bauprodukte e.V., Düsseldorf)

-

According French VOC  
Classification

**A+**



solvent-free

### EPD (Environmental Product Declaration)

ARDEX R 5 E corresponds to FEICA EPD:

**EPD-FEI-20150298-IBG1-EN**

### Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE RE30** – epoxy resin products, sensitizing, total solid

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)



# ARDEX R 5 E

Fast Cure Epoxy Primer

## Sustainable Building

According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

### Version 2018

#### DGNB criteria ENV 1.2: Local environmental impact

ARDEX R 5 E can be classified as epoxy surface coating of floor, ceiling and wall – also in system structures.

**ARDEX R 5 E fulfills the requirements for Quality Level 2.**

### Version 2015

#### DGNB criteria ENV 1.2: Local environmental impact

ARDEX R 5 E can be classified as epoxy surface coating of floor, ceiling and wall – also in system structures.

Notice: For products up to 5 % of BGFa (DIN 277) no documentation is required.

ARDEX R 5 E has the GISCODE RE30.

**ARDEX R 5 E fulfills the requirements for Quality Level 2.**

According LEED (Leadership in Energy and Environmental Design)

### Version 4 (2014)

#### EQ: Low Emitting Materials

ARDEX R 5 E does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

**ARDEX R 5 E does not meet the requirements.**

#### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX R 5 E corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX R 5 E fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

### Version 2009

#### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category ‘Architectural Sealant Primers –nonporous‘ according SCAQMD Rule 1168 is 250 g/L. The VOC value of ARDEX R 5 E according SCAQMD Rule 1168 is < 250 g/L.

**ARDEX R 5 E meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

#### MR Credit 5.1 und 5.2: Regional Materials

##### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
www.ardex.de

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
kundendienst@ardex.de  
www.ardex.de



## Sustainable Building

# ARDEX R 5 E

## Fast Cure Epoxy Primer

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 15/12/2020

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

