

Sustainability data sheet

ARDEX X 78 S

Rapid Microtec Flexible Floor Tile Adhesive

Semi-pourable consistency is ideal for solid bed fixing large format floor tiles without having to butter the backs.

Rapid setting characteristics allow tiles to be trafficked and grouted after 90 minutes.

Emissions

According to GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf) -

According to French VOC Classification **A+**



solvent-free

EPD (Environmental Product Declaration)

ARDEX X 78 S corresponds to FEICA EPD:

EPD-DBC-20220218-IBF1-EN

Technical Assessment

Meets the C2 requirements according to EN 12004

C2 FE, Cement mortar for increased requirements with additional characteristic values early adhesive strengths (F) and extended open time (E).

Meets the S1 requirements according to EN 12002

S1 deformability > 2,5 mm

According to GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

GISCODE ZP1 – cementitious product, low-chromate

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX X 78 S

Rapid Microtec Flexible Floor Tile Adhesive

Sustainable Building

According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

Version 2018

DGNB criteria ENV 1.2: Local environmental impact

ARDEX X 78 S can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX X 78 S has the GISCODE ZP1. This GISCODE is no evaluation-relevant factor according DGNB.

ARDEX X 78 S fulfills the requirements for highest Quality Level 4.

Version 2015

DGNB criteria ENV 1.2: Local environmental impact

ARDEX X 78 S can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX X 78 S has the GISCODE ZP1.

ARDEX X 78 S fulfills the requirements for highest Quality Level 4.

According LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX X 78 S does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

ARDEX X 78 S does not meet the requirements.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX X 78 S corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX X 78 S fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX X 78 S according SCAQMD Rule 1168 is < 65 g/L.

ARDEX X 78 S meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX X 78 S

Rapid Microtec Flexible Floor Tile Adhesive

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship.

Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 10/03/2023

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de

